

PRODUCT DESCRIPTION

Akona® Gray Pourable Concrete Crack Filler is a ready mixed, pourable material for filling narrow horizontal cracks up to ¼ in. deep x ¼ in. wide (6x6 mm). It is gray in color to blend with concrete surfaces and is flexible to conform to movements of active cracks. For larger static cracks and holes, use Akona® Vinyl Cement Patch or with wider active moving cracks, a polyurethane sealant is recommended.

WHEN/WHERE TO USE

For filling narrow holes / cracks in:

- Interior and exterior applications
- Sidewalks, steps, driveways
- Floors, slabs, and patios

ADVANTAGES

- Ready to use - no mixing required
- Flexible
- Gray in color

AVAILABLE SIZES

- 1 qt. (0.95 L) bottle (BOM #102638)
- 1 gal. (3.8 L) bottle (BOM #102639)

COVERAGE

- 1 qt. bottle fills 40 lin. ft. (12.2 m) at ¼ in. deep x ¼ in. (6 mm) wide
- 1 gal. bottle fills 160 lin. ft. (48.7 m) at ¼ inch deep x ¼ inch (6 mm) wide



PREPARATION

Read all directions before starting work. Always remove all loose and unsound materials. Thoroughly clean all surfaces of dirt, dust, grease, or other contaminants which could interfere with bonding. Deep cracks should be filled with clean fine sand or backer rod within ¼ in. of the surface. For better adhesion, surfaces should be dry.

MIXING

Shake bottle to ensure a uniform mix before application. Prior to use, place container in a warm location or submerge in hot water for better flowability.

APPLICATION

For best results, apply when temperatures are above 50°F (10°C) within 48 hours of application and when no rain is expected within 24 hours. Gray Pourable Concrete Crack Filler cures by air drying; therefore, cooler temperatures will retard drying while higher temperatures will accelerate drying. Clip spout close to the end for narrow cracks and at a wider point for larger cracks. Pour into the crack and fill only to ⅛ in. (3 mm) from surface. This technique will allow foot and vehicle traffic to resume immediately on narrow cracks. Clean up with soap and warm water as soon as application is completed. Protect new surfaces from use until material is completely hard and set. Painting this product is not recommended.

CLEAN UP

Typically water will satisfactorily clean tools after using Gray Pourable Concrete Crack Filler. If the material has begun to harden, warm soapy water may be helpful for cleaning hands and tools.

Proper application and installation of all AKONA products are the responsibility of the end user.



KEEP FROM FREEZING

WARNING: INJURIOUS TO EYES

KEEP OUT OF REACH OF CHILDREN



WARNING

Always read the product SDS and cautionary statements on product container prior to application. Wear proper protective gear as advised on the label and/or SDS. Wash hands thoroughly with warm, soapy water after handling or before eating. Do not take internally. KEEP OUT OF REACH OF CHILDREN.

WARRANTY

Seller warrants that its product will conform to and perform in accordance with the product specifications. The foregoing warranty is in lieu of all other warranties, expressed or implied, including, but not limited to those concerning merchantability and fitness for a particular purpose. Because of the difficulty in ascertaining and measuring damages hereunder, it is agreed that, Seller's liability to the Buyer shall not exceed the total amount billed and billable to the Buyer for the product hereunder.

Helpful Items:



Safety Glasses



Brush



Gloves