

PRODUCT DESCRIPTION

Akona® Instant Post Cement is used for quick setting of all metal, wood and plastic fence, mailbox, basketball, and swing-set posts. This product does not require pre-mixing prior to use. Instant Post Cement is not designed to be used for footings or structural supports.

WHEN/WHERE TO USE

- Fence posts
- Mail boxes
- Basketball poles
- Swing sets

ADVANTAGES

- No mixing required
- Fast setting - sets in minutes
- High strength
- Just add water

AVAILABLE SIZE

- 50 lb. (22.7 kg) bag (BOM #102631)

COVERAGE/YIELD

See table below.

APPLICATION

Read all directions before starting work.

1) Use approximately 1 gal. (3.8 L) of water per 50 lb. bag of Instant Post Cement. Water amount may vary depending on soil type and conditions.


2) Depending on the number of bags being used, add about ¾ of the required water into the hole.

3) Pour Instant Post Cement into the hole using a circular motion stopping about 3-4" below the ground level. Tamp mixture to remove air pockets.

4) Pour balance of the required water into hole. Re-tamp mixture making sure no dry cement remains.



Helpful Items:



5) Align the post to desired level and height prior to setting additional posts. In 10-20 minutes, you'll have a properly set post.

6) After Instant Post Cement has fully set, fill the remainder of the hole with sod or soil.

CLEAN UP

Typically water will satisfactorily clean tools after using. If the material has begun to harden, warm soapy water may be helpful for cleaning hands and tools.

IMPORTANT NOTES

- Dig post hole deeper than frost line.
- Do not use for structural supports.
- Use only when both ground and air temperatures are above 40° F (4°C) and below 100°F (38°C) within 24 hours of application and 72 hours thereafter.
- Avoid machine or hand mixing due to rapid set time.
- Build up top of cement mix to a sloped pyramid shape around post so rain or water will not puddle at the base of the post.
- Temperature, humidity and soil absorbency may cause the set time to vary slightly. Cooler weather will slightly retard set time – hot weather will slightly accelerate set time.

Proper application and installation of all AKONA products are the responsibility of the end user.



WARNING: INJURIOUS TO EYES

KEEP OUT OF REACH OF CHILDREN

WARNING

Always read the product SDS and cautionary statements on product container prior to application. Wear proper protective gear as advised on the label and/or SDS. Wash hands thoroughly with warm, soapy water after handling or before eating. Do not take internally. **KEEP OUT OF REACH OF CHILDREN.**

WARRANTY

Seller warrants that its product will conform to and perform in accordance with the product specifications. The foregoing warranty is in lieu of all other warranties, expressed or implied, including, but not limited to those concerning merchantability and fitness for a particular purpose. Because of the difficulty in ascertaining and measuring damages hereunder, it is agreed that Seller's liability to the Buyer shall not exceed the total amount billed and billable to the Buyer for the product hereunder.

HOLE DEPTH	2"-3" Post			4" Post		
	HOLE DIAMETER			HOLE DIAMETER		
	6"	8"	12"	6"	8"	12"
12"	½	¾	1¼	⅓	⅔	1¼
24"	1	1½	2½	1	1⅓	2¼
36"	1½	2¼	3¾	1	2	3¼
48"	2	3	5	1⅓	2⅔	4½
	bags needed			bags needed		