

PRODUCT DESCRIPTION

Akona® Mortar Repair is designed for tuck-pointing, repairing, and sealing mortar joints and cracks in masonry units such as stone, brick and block walls. The product is gray in color and designed to blend in with the texture of surrounding mortar. Mortar Repair is a sanded acrylic formulation that is fast drying, paintable and provides superior adhesion to masonry. For maximum joint width $\frac{3}{8}$ in. (9.6 mm) and maximum depth $\frac{3}{8}$ in.

WHEN/WHERE TO USE

- Fills mortar joints
- Vertical repairs
- Masonry finish

ADVANTAGES

- Ready to use
- Superior adhesion
- Durable and flexible
- Fast drying

AVAILABLE SIZE

- 10.1 oz. (0.3 L) tube (BOM #103174)

COVERAGE


- 10.1 oz. yields approximately 10 lin. ft. (3 m) at $\frac{3}{8}$ x $\frac{3}{8}$ in. (9.6x9.6 mm) joint

PREPARATION

Read all directions before starting work. Remove all loose or unsound materials.



Helpful Items:



Thoroughly clean surface of dirt, dust, grease or other contaminants. Be sure to remove all loose chips or stones from the joint prior to using Mortar Repair. Apply to dry surfaces only for best bonding.

APPLICATION

Trim cartridge to desired bead size. Use cartridge in standard caulking gun. Use in joints of maximum width and depth of $\frac{3}{8}$ " (9.6 mm). Deep cracks can be partially filled with sand or backer rod prior to application. The repair can be tooled to even out the surface. Excess material may be cleaned with a damp cloth while wet.

CLEAN UP

Typically water will satisfactorily clean tools after using Mortar Repair if the material has begun to harden, warm soapy water may be helpful for cleaning hands and tools.

FOR BEST RESULTS

- Do not use for structural repairs to a badly damaged wall
- Wait at least 24 hours before painting
- Use latex paints only
- Air and surface temperature should be above 40°F (4°C) for proper application
- Do not apply if rain threatens or is predicted within 12 hours
- Store between 35°F and 100°F (2°C and 38°C)

Proper application and installation of all AKONA products are the responsibility of the end user.

WARNING

Always read the product SDS and cautionary statements on product container prior to application. Wear proper protective gear as advised on the label and/or SDS. Wash hands thoroughly with warm, soapy water after handling or before eating. Do not take internally. **KEEP OUT OF REACH OF CHILDREN .**

WARRANTY

Seller warrants that its product will conform to and perform in accordance



with the product specifications. The foregoing warranty is in lieu of all other warranties, expressed or implied, including, but not limited to those concerning merchantability and fitness for a particular purpose. Because of the difficulty in ascertaining and measuring damages hereunder, it is agreed that Seller's liability to the Buyer shall not exceed the total amount billed and billable to the Buyer for the product hereunder.



KEEP FROM FREEZING

WARNING: INJURIOUS TO EYES

KEEP OUT OF REACH OF CHILDREN