

## PRODUCT DESCRIPTION

Akona® Premium Concrete Repair is a quick setting repair product ideally suited for vertical applications. This product combines the superior bonding and abrasion resistance of our polymer system with the strength of Portland cement. The result is a patch that is strong and durable. Use for repairs up to ½ in. (13 mm) depth per application. The small, convenient sized container can be used for mixing the product.

## WHEN/WHERE TO USE

- Filling chipped concrete in steps, sidewalks, floors, etc.
- Repairing small holes in concrete or masonry
- Small vertical and horizontal repairs

## ADVANTAGES

- High strength with superior adhesion
- Polymer-modified, add clean water, mix, and use
- Resistant to freeze-thaw cycles
- Quick drying

## AVAILABLE SIZE

- 4 lbs. (1.8 kg) tub (BOM #102637)

## COVERAGE

One tub covers approximately 3.5 sq. ft. (0.32 m<sup>2</sup>) when applied at ¼ in. (3 mm) thick.

## PREPARATION

Read all directions before starting work. Thoroughly clean surface of dirt, dust, oil, loose material and all contaminants.

## MIXING

Mix with water at a rate of 2 oz. (0.06 L) of clean water to 1 lb. (0.45 kg) of dry powder. Always add powder to liquid to avoid lumps using a clean container and clean tools. Proper consistency is a stiff, putty-like mixture. Mix using water only, a bonding agent is not needed.

## APPLICATION

Pre-dampen surface, but leave no standing water. Force material into place with a trowel or wide blade putty knife to make sure material makes good contact with the surface to be repaired. After 10-15 minutes, the material may be shaped or shaved with a trowel to get a desired look. Additional layers may be used to build-up depths greater than ½ in. Allow 2-4 hours between layers. Apply only to surfaces that are frost free and are between 40°F-100°F (4.4°C- 38°C) within 24 hours of application and 48 hours thereafter, and when rain is not forecast for 24 hours.



## CURING

Sets in 4 hours at 70°F (21°C) at ¼ in. thickness. Allow 8 hours curing time before permitting vehicle traffic. (Curing time may vary slightly due to temperature and humidity conditions.) If applied in direct sunlight, or when temperatures exceed 70°F (21°C), lightly spray surface with water once daily for 2 days.

## CLEAN UP

Typically water will satisfactorily clean tools after using the product. If the material has begun to harden, warm soapy water may be helpful for cleaning hands and tools. Dried material requires mechanical removal.

*Proper application and installation of all AKONA products are the responsibility of the end user.*



**WARNING: INJURIOUS TO EYES**

**KEEP OUT OF REACH OF CHILDREN**

## WARNING

Always read the product SDS and cautionary statements on product container prior to application. Wear proper protective gear as advised on the label and/or SDS. Wash hands thoroughly with warm, soapy water after handling or before eating. Do not take internally. **KEEP OUT OF REACH OF CHILDREN**

## WARRANTY

Seller warrants that its product will conform to and perform in accordance with the product specifications. The foregoing warranty is in lieu of all other warranties, expressed or implied, including, but not limited to those concerning merchantability and fitness for a particular purpose. Because of the difficulty in ascertaining and measuring damages hereunder, it is agreed that, Seller's liability to the Buyer shall not exceed the total amount billed and billable to the Buyer for the product hereunder.



## Helpful Items:

