

PRODUCT DESCRIPTION

Akona® Pre-Mixed Concrete Patch is a water-based formula intended to patch minor cracks, holes, and surface defects in concrete or masonry. Product may also be used for residential repairs of masonry walls and re-applying small broken pieces of concrete or tuck pointing brick mortar joints. Pre-Mixed Concrete Patch offers superior adhesion and may be used for vertical or horizontal patches.

WHEN/WHERE TO USE

- Interior and exterior
- Repairs holes or cracks
- Vertical and horizontal patches
- Concrete or masonry surfaces

ADVANTAGES

- Ready to use
- Easy to apply
- Gray cement color
- Durable and flexible
- Non-flammable

AVAILABLE SIZE

- 1 qt. (0.95 L) tub (BOM #103962)

COVERAGE

- 1 qt. yields approximately 3 sq. ft. (0.28 m²) at 1/8 in. (3 mm) thickness



Helpful Items:



PREPARATION

Read all directions before starting work. Always remove all loose and unsound materials prior to application. Thoroughly clean all surfaces of dirt, dust, grease, paint, or other contaminants which could interfere with bonding. For best adhesion, surfaces should be dry and frost free.

APPLICATION

Gently stir product before use. Remove product directly from container and apply with a trowel or putty knife. Press firmly into patch area. Smooth finished patch with damp application tool. DO NOT OVER TROWEL. Do not apply if rain is expected or temperature is likely to fall below 50°F (10°C) within 12 hours. Maximum application thickness is 1/4 in. (6.3 mm). When applying multiple layers, allow 2-4 hours drying between layers. For larger patches, use Akona Vinyl Cement Patch.

CURING/PAINTING

Product will harden within a few hours. Wait until the product fully cures before painting. Allow a minimum of 7 days for product to fully cure when temperatures are between 65°-75°F (18°-24°C) with no rain. Use a high-quality, exterior masonry grade, breathable acrylic latex paint. Prime the surface prior to applying paints on Pre-Mixed Concrete Patch.

CLEAN UP

Typically water will satisfactorily clean tools after using Pre-Mixed Concrete Patch. If the material has begun to harden, warm soapy water may be helpful for cleaning hands and tools. Dried material will require mechanical removal.

Proper application and installation of all AKONA products are the responsibility of the end user.



KEEP FROM FREEZING

WARNING: INJURIOUS TO EYES

KEEP OUT OF REACH OF CHILDREN

WARNING

Always read the product SDS and cautionary statements on product container prior to application. Wear proper protective gear as advised on the label and/or SDS. Wash hands thoroughly with warm, soapy water after handling or before eating. Do not take internally. KEEP OUT OF REACH OF CHILDREN

WARRANTY

Seller warrants that its product will conform to and perform in accordance with the product specifications. The foregoing warranty is in lieu of all other warranties, expressed or implied, including, but not limited to those concerning merchantability and fitness for a particular purpose. Because of the difficulty in ascertaining and measuring damages hereunder, it is agreed that, Seller's liability to the Buyer shall not exceed the total amount billed and billable to the Buyer for the product hereunder.