

PRODUCT DESCRIPTION

Akona® Pre-Mixed Stucco Patch is a ready to use formula intended to patch cracks, holes, and surface defects in stucco up to ¼ in. (6 mm) thick. This product offers a durable and flexible finish that blends with the existing stucco. Pre-Mixed Stucco Patch offers superior adhesion and can be used on interior or exterior stucco surfaces. Product may be primed and painted with most paints.

WHEN/WHERE TO USE

- Interior and exterior repairs
- Repairs holes and cracks
- Vertical and horizontal repairs

ADVANTAGES

- Ready to use
- Non shrink
- Durable and flexible
- Non-flammable

AVAILABLE SIZE

- 1 qt. (0.95 L) tub (BOM #102728)

COVERAGE

- 1 qt. will yield approximately 3 sq. ft. (0.28 m²) at ¼ in. (3 mm) thickness.



PREPARATION

Read all directions before starting work. Thoroughly clean surface of loose material, dirt, dust, oil, paint, and all contaminants with a stiff brush or stream of water. For best adhesion, surfaces should be dry and frost free prior to application of Pre-Mixed Stucco Patch.

MIXING

No mixing is required, gently stir product before use. Do not dilute with water or solvents.

APPLICATION

Remove product directly from container and apply with a trowel or putty knife, pressing material into the surface to improve bond. Spread and texture to match existing stucco pattern. Maximum application thickness is ¼ in. (6 mm) in a single application. For deeper repairs, apply this product in ¼ in. lifts, allowing each layer to dry 2-4 hours between layers. Do not apply if rain is expected or if air or surface temperatures are likely to fall below 50°F (10°C) within 48 hours.

CURING/PAINING

Product will harden within a few hours. Wait until the product fully cures before painting. Allow a minimum of 7 days for product to cure when temperatures are between 65°-75°F (18°-24°C) with no rain. Use a high-quality, exterior masonry grade, breathable acrylic latex paint. Prime the surface prior to applying paints on Pre-Mixed Stucco Patch.

CLEAN UP

Typically warm soapy water will satisfactorily clean tools while product is still wet. Dried product is insoluble in water. Hardened product remaining on tools may be removed with mineral spirits or mechanical abrasion.

Proper application and installation of all AKONA products are the responsibility of the end user.



WARNING

Always read the product SDS and cautionary statements on product container prior to application. Wear proper protective gear as advised on the label and/or SDS. Wash hands thoroughly with warm, soapy water after handling or before eating. Do not take internally. **KEEP OUT OF REACH OF CHILDREN**

WARRANTY

Seller warrants that its product will conform to and perform in accordance with the product specifications. The foregoing warranty is in lieu of all other warranties, expressed or implied, including, but not limited to those concerning merchantability and fitness for a particular purpose. Because of the difficulty in ascertaining and measuring damages hereunder, it is agreed that, Seller's liability to the Buyer shall not exceed the total amount billed and billable to the Buyer for the product hereunder.

Helpful Items:



Safety Glasses



Trowel



Putty Knife



Gloves

KEEP FROM FREEZING

WARNING: INJURIOUS TO EYES

KEEP OUT OF REACH OF CHILDREN