








	Medium-Duty Refractory Mortar	Non Shrink Grout	White Glass Block Mortar	Instant Post Cement	Instant Anchoring Cement	Fast-Setting Anchoring Epoxy	Instant Water Stop
							
Uses/ Advantages	<ul style="list-style-type: none"> For fireplaces, fire pits, flues, etc. Good for applications up to 2550°F Air entrained for freeze-thaw resistance One hour working time ASTM C199 	<ul style="list-style-type: none"> Capable of handling high load transfers MN DOT approved <i>Non-Shrink Grouts</i> ASTM C1107 Corps of engineers spec. CRD-C 621 	<ul style="list-style-type: none"> For use with glass block in shower or bathroom walls High-strength white mortar Minimizes joint shrinkage Mix with bonding additive for exterior applications 	<ul style="list-style-type: none"> Sets fence posts, mailboxes, basketball poles, and swing sets No mixing required No bracing required Fast-setting Not for structural supports (footings) 	<ul style="list-style-type: none"> Expands as it hardens Sets handrails, bolts, poles, and fixtures Use with concrete or masonry Sets in 20 minutes 	<ul style="list-style-type: none"> High-strength Resists chemicals and solvents Moisture tolerant 100% solids Fast-setting Non-sag 	<ul style="list-style-type: none"> Bonds well to wet walls Sets in just 3-5 minutes Plugs holes in walls Seals water flow in basements Great for swimming pool repairs
Approximate Coverage	<ul style="list-style-type: none"> 50 lb. bag yields .5 cu. ft. of wet mortar Will lay 80-100 standard fire bricks at 1/8" joint thickness 	<ul style="list-style-type: none"> 50 lb. bag yields 0.45 cu. ft., at a flowable consistency of wet mortar 	<ul style="list-style-type: none"> 50 lb. bag yields .5 cu. ft. of wet mortar 	<ul style="list-style-type: none"> 50 lb. bag will set a 3" post in a 6" diameter hole with a depth of 24" 	<ul style="list-style-type: none"> 10 lb. yields 170 cu. in. or anchors 2 fixtures in a 2" diameter hole with a depth of 2" 	<ul style="list-style-type: none"> 8.45 fl. oz. tube yields 30 lin. ft. at a 1/8" x 1/8" line 	<ul style="list-style-type: none"> 10 lb. yields 18 cu. in. or a crack 1" deep by 1/4" wide and 6' long 25 lb. yields 45 cu. in. or a crack 1" deep by 1/4" wide and 15' long
Application							
Interior & Exterior	X	X	X	X	X	X	X
Pre-Blended: Just Add Water	X	X	X	X	X	Ready to use	X
Fast-Setting				X	X	X	X
Setting Fireplace Masonry Units	X						
Setting Glass Block			X				
Load Transfer And Base Weight Distribution		X					
Setting Large Fixtures (6-12" diameter hole)				X			
Setting Small Fixtures (2-6" diameter hole)		X			X	X	
Creates Moisture Resistance							X
High Strength / Bond	X	X	X	X	X	X	X
Expands As It Sets					X		X
Low/Non-Shrink		X	X			X	