

## **CONCRETE PATCHES SELECTION GUIDE**



	VINYL CEMENT PATCH	AKONAKOTE <sup>®</sup> POURABLE CONCRETE PATCH	INSTANT PATCHING CEMENT	PRE-MIXED CONCRETE & STUCCO PATCH
		<image/> <image/> <section-header><section-header><section-header><section-header><section-header><section-header></section-header></section-header></section-header></section-header></section-header></section-header>		
USES & Advantages	<ul> <li>Superior bond</li> <li>High strength</li> <li>Polymer-modified</li> <li>Sets in 24 hours</li> <li>Trowelable from featheredge up to ½" per layer</li> </ul>	<ul> <li>Patch seams, holes, and cracks</li> <li>Use to prepare floors for resurfacing</li> <li>Flowable/pourable</li> <li>Correct defects up to ½"</li> </ul>	<ul> <li>Self bonds to existing concrete</li> <li>Ideal for deep repairs</li> <li>Sets in just 90 minutes</li> <li>Correct defects up to 2" or up to 5" when mixed with pea gravel</li> </ul>	<ul> <li>Ready to use</li> <li>Easy to apply</li> <li>Durable and flexible</li> <li>Concrete or masonry surfaces</li> <li>Gray color</li> <li>Correct defects up to ¼"</li> </ul>
COVERAGE	<ul> <li>10 lb. will yield 10 sq. ft. at 1/6" thickness</li> <li>25 lb. will yield 25 sq. ft. at 1/6" thickness</li> <li>40 lb. will yield 40 sq. ft. at 1/8" thickness</li> </ul>	• 50 lb. will yield 50 sq. ft. at $\frac{1}{8}$ " thickness	<ul> <li>10 lb. fills a crack 1" wide x ½" deep (30 ft. length) or 10 sq. ft. at ½" thickness</li> </ul>	• 1 qt. will yield 3 sq. ft. at 1/8" thickness
		APPLICATION	·	
Interior & Exterior	Х	Х	Х	Х
Fix Defects Prior to Resurfacing	х	x	x	
Pourable/Flowable		Х		
Can Be Extended For Deeper Repairs			X	
Can Be Applied In Multiple Layers For Deeper Repairs	Х			Х
Overhead Applications				
Trowelable to Featheredge	Х	Х		Х
Fast-Setting			X	
Ready to Use (No Mixing)				X
Pre-Blended Mixing Liquid:	Water only	Water only	Water or Bonding Additive	
For Concrete Surfaces	Х	Х	Х	Х
For Mortar, Stucco, Stone				