# Other great landscape products by





# RESTORATION CLEANER Removes efflorescence

Removes efflorescence and other stains from pavers, concrete, and stone



#### PAVER BONDING MORTAR

Adhere pavers to steps, walkways, patios, and other concrete surfaces



### **REFRACTORY MORTAR**

Rated up to 2,500°F for fire pits, fireplaces, and pizza ovens



#### **COUNTERTOP MIX**

Create gorgeous outdoor kitchen tops, bars, or tables. Sets in 18 hours!



#### STONE VENEER MORTAR

Apply masonry veneer to fire pits, ovens, posts, fireplaces, and more



# CHERRY STONE GRIT A natural alternative to

salt for winter traction. Environmentally safe!



#### Available At:



# LANDSCAPE LOC<sup>®</sup> Mulch & Rock Bond



## **USES**:

- Keeps mulch & other ground cover in place
- Reduces landscape maintenance
- Mulch, rock, sand, leaves, gravel, etc.
- Keeps mulch from blowing into pools & ponds
- Controls dust & erosion on gravel roads

#### **ADVANTAGES:**

- Easy to apply with a sprayer
- Reaches full bond in 24-48 hours
- Goes on white & dries clear
- Allows surface to drain & breathe
- Environmentally safe
- Non-toxic safe for plants, kids, and pets
- Low VOC & EPA compliant



Nurserymen's Preferred® Landscape Loc® Mulch & Rock Bond is a specially—formulated locking compound designed to stabilize mulch, rock, gravel, sand, and other ground cover.



Landscape Loc Mulch & Rock Bond prevents movement caused by rain, wind, wildlife, leaf blowers, mowers pets, edgers, and other sources while allowing the substrate to drain and breath. Landscape Loc Mulch & Rock Bond also protects, sustains, and enhances the natural look of your mulch. Lower your maintenance time and expenses. Excellent for areas around pools or ponds to prevent mulch from becoming pool or pond debris.



# DIRECTIONS FOR USE

PREPARATION: Place new mulch or arrange existing mulch to desired location and thickness. Apply when temperatures are above 50°F and when no wind or rain is expected within 24 hours. (Bond time will be longer with colder temperatures and shorter with higher temperatures.)

## APPLICATION:

- SHAKE WELL BEFORE EACH USE
- Hold sprayer 1-2 feet away from surface
- Spray light or heavy for desired bond
- Product goes on white and dries clear
- Allow 24-48 hours to dry completely
- Allow to dry before walking on area
- Apply a second coat when necessary
- Reapply annually for best results
- Best when used during the same growing season as purchased



CLEAN UP: Excess product can be cleaned with water before product has dried. Use soap and water to clean dried product.

COVERAGE: Approximately 750-1,500 sq. ft. per gallon (depending on thickness)

# **AVAILABLE SIZES:**

- 1 Gallon Bottles (3.78 Liters)
- 5 Gallon Pails (18.9 Liters)

## **SHAKE WELL BEFORE USE!**

#### PROTECT FROM FREEZING

KEEP OUT OF REACH OF CHILDREN

WARRANTY: Seller warrants that its product will conform to and perform in accordance with the product specifications. The foregoing warranty is in lieu of all other warranties, express or implied, including, but not limited to, those including merchantability and fitness for a particular purpose. Because of the difficulty in ascertaining and measuring damages hereunder, it is agreed that, the Seller's liability to the Buyer shall not exceed the total amount billed and billable to the Buyer for the product hereunder.

CAUTION: Vapors may cause irritation of eyes, nose, and throat. May cause skin sensitization or other allergic responses. HARMFUL IF SWALLOWED. Do not breathe vapors. Use with adequate ventilation. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. Close container after each use. Do not transfer into unmarked container.

KEEP OUT OF REACH OF CHILDREN.

USE IN THE SAME GROWING SEASON AS PURCHASED

# Manufactured by:



SPEC BLENDED CONSTRUCTION PRODUCTS®

TCC MATERIALS

2025 Centre Pointe Blvd., Suite 300 Mendota Heights, MN 55120