



 Restoration Cleaner: removes efflorescence and other stains from pavers, concrete, and stone



 Paver Bonding Mortar: adhere pavers to steps, walkways, patios, and other concrete surfaces



 Refractory Mortar: rated up to 2,500°F for fire pits, fireplaces, and pizza ovens



• Countertop Mix: create gorgeous outdoor kitchen tops, bars, or tables. Sets in 18 hours!



Stone Mortar Mix: apply masonry veneer to fire pits, ovens, posts, fireplaces, and more



cherry Stone Grit: a natural alternative to salt for winter traction. Environmentally safe!



Available At:





LANDSCAPE LOC®

Mulch & Rock Bond



#### **Uses:**

- Keeps mulch & other ground cover in place
- Reduces landscape maintenance
- Mulch, rock, sand, leaves, gravel, etc.
- Keep mulch from blowing into pools & ponds
- Control dust & erosion on gravel roads

# **Advantages:**

- Easy to apply with a sprayer
- Reaches full bond in 24-48 hours
- Just shake well and use
- Goes on white & dries clear
- Allows surface to drain & breath
- Environmentally safe
- Non-toxic safe for plants, kids, and pets
- Low VOC & EPA compliant
- Lasts all season!

© 2013 TCC Materials®

**PATENT PENDING** 



Nurserymen's Preferred Landscape Loc® Mulch & Rock Bond is a specially - formulated locking compound designed to stabilize mulch, rock, gravel, sand, and other ground cover.



Landscape Loc Mulch & Rock Bond

prevents movement caused by rain, wind, wildlife, leaf blowers, mowers pets, edgers, and other sources while allowing the substrate to drain and breath. Landscape Loc Mulch & Rock Bond also protects, sustains, and enhances the natural look of your mulch. Lower your maintenance time and expenses. Excellent for areas around pools or ponds to prevent mulch from becoming pool or pond debris.



# DIRECTIONS FOR USE

Preparation: Place new mulch or arrange existing mulch to desired location and thickness. Apply when temperatures are above 50°F and when no wind or rain is expected within 24 hours. (Bond time will be longer with colder temperatures and shorter with higher temperatures.)

# Application:

- Shake well before use
- Hold sprayer 1-2' away from surface
- Spray light or heavy for desired bond
- Product goes on white and dries clear
- Allow 24-48 hours to dry completely
- Allow to dry before walking on area
- Apply a second coat when necessary
- Reapply annually for best results
- If settling occurs in container, shake well to remix



**Clean Up:** Excess product can be cleaned with water before product has dried. Use soap and water to clean dried product.

**Coverage:** One gallon will cover up to 1,500 sq. ft. with light use or up to 750 sq. ft. with heavy-duty use. (Coverage varies depending on weight of material & desired hold.)

### Available Sizes:

- 1 Gallon Bottles (3.78 Liters)
- 5 Gallon Pails (18.9 Liters)

#### **SHAKE WELL BEFORE USE!**

PROTECT FROM FREEZING

**KEEP OUT OF REACH OF CHILDREN** 

WARRANTY: Seller warrants that its product will conform to and perform in accordance with the product specifications. The foregoing warranty is in lieu of all other warranties, express or implied, including merchantability and fitness for a particular purpose. Because of the difficulty in ascertaining and measuring damages hereunder, it is agreed that seller's liability to the buyer at no point, for any particular project, shall exceed the total purchase price of said product.

WARNING: Avoid contact with eyes and skin. If contact with eyes occurs, flood eyes repeatedly with clean water and seek a physician's care immediately. Do not rub eyes. Wash hands thoroughly with warm, soapy water after handling or before eating. Do not take internally. KEEP OUT OF REACH OF CHILDREN.

Manufactured by:



SPEC BLENDED CONSTRUCTION PRODUCTS™

TCC MATERIALS 2025 Centre Pointe Blvd., Suite 300 Mendota Heights, MN 55120