



CEMENT & CONCRETE PRODUCTS™

MASON SAND

PRODUCT No. 1952

PRODUCT DESCRIPTION

QUIKRETE® Mason Sand is suitable for field-preparation of mortar.

PRODUCT USE

A washed, properly graded fine masonry sand.

Use for:

Mix with QUIKRETE® Portland Cement & Hydrated Lime - Type S or with QUIKRETE® Masonry Cement to make Base Type N or Type S mortars:

To make mortar, mix QUIKRETE® Mason Sand with QUIKRETE® Portland Cement and QUIKRETE® Hydrated Lime - Type S or QUIKRETE® Portland-Lime Cement in accordance with ASTM C 270. Alternately, mix QUIKRETE® Mason Sand with QUIKRETE® Masonry Cement in accordance with ASTM C270.

Meets ASTM C144 specifications

SIZES

- QUIKRETE® Mason Sand - 50 lb (22.7 kg) bags

DIVISION 32

Aggregate
32 15 00



YIELD

- Each 50 lb (22.7 kg) bag of QUIKRETE® Mason Sand contains approximately 0.6 cu ft (17L) of sand by volume

PRECAUTIONS

- Not suitable for sandblasting

WARRANTY

The QUIKRETE® Companies warrant this product to be of merchantable quality when used or applied in accordance with the instructions herein. The product is not warranted as suitable for any purpose or use other than the general purpose for which it is intended. Liability under this warranty is limited to the replacement of its product (as purchased) found to be defective, or at the shipping companies' option, to refund the purchase price. In the event of a claim under this warranty, notice must be given to The QUIKRETE® Companies in writing. This limited warranty is issued and accepted in lieu of all other express warranties and expressly excludes liability for consequential damages.

The QUIKRETE® Companies
One Securities Centre
3490 Piedmont Rd., NE, Suite 1300, Atlanta, GA 30305
(404) 634-9100 • Fax: (404) 842-1425

* Refer to www.quikrete.com for the most current technical data, MSDS, and guide specifications

