

©Roberts Concrete Products (a TCC Materials company) Version 1.2

Roberts Concrete Products

2025 Centre Pointe Boulevard, Suite 300 Mendota Heights, MN 55120-1221 Emergency Telephone Number: 651-688-9116 Information Telephone Number 651-688-9116 Revision Date June 2018

## Section 1: Product Identification

Product Type: Coal Slag

#### Product Name:

SAKRETE Ash Tray Sand (Black)

### Section 2: Hazard Identification

Stable, amorphous glass-like compounds.

### OSHA (29 CFR 1910.1200) Hazard Classification of Coal Slag (CAS # 68476-96-0) Specific Target Organ Toxicity (STOT) - Repeated Exposure, Category 2

(Respiratory System)

#### GHS LABEL ELEMENTS Symbol(s)



Signal Word WARNING

## Hazard Statement(s)

May cause damage to respiratory system, lungs (pulmonary fibrosis) through prolonged or repeated exposure.

## **Precautionary Statement(s)**

#### Prevention

Do not breathe dusts.

### Response

Get medical advice/attention if you feel unwell.

#### Disposal

Dispose of contents in accordance with federal, state/provincial and local regulations.

Hazards not otherwise classified:	None known.
Unknown Acute Toxicity Statement (Mixture):	None known.



©Roberts Concrete Products (a TCC Materials company) Version 1.2

### Section 3: Hazardous Ingredients/Composition

Component	Percent %	CAS
Amorphous Fused Silicon Dioxide	48-50	60676-86-0
Aluminum oxide	18-22	1344-28-1
Iron oxide	18-22	1309-37-1
Calcium Oxide	5-7	1305-78-8
Potassium Oxide	1-2	12136-45-7
Titanium Oxide	0-1	13463-67-7
Magnesium Oxide	0-1	1309-48-4
Sodium Oxide	0-1	1313-59-3
Crystalline Silica as Quartz	0-0.1	14808-60-7
Crystalline Silica as Cristobalite	0-0.1	14464-46-1
Beryllium	0-0.0005	7440-41-7

### Section 4: First Aid Measures

# Description of Necessary Measures

Inhalation:

Remove to fresh air. Get immediate medical attention if you feel unwell.

Skin:

Product is not a skin sensitizer. Wash skin thoroughly with water and soap.

Remove contaminated clothing. Get medical advice/attention if symptoms occur. **Eye contact:** 

Immediately flush eyes with plenty of water for at least several minutes. Remove contact lenses, if present and easy to do. Do not rub eyes. Continue rinsing. If irritation persists, get medical attention.

#### Ingestion:

If a large amount is swallowed, rinse out mouth. Give water to drink. Do NOT induce vomiting. Get medical attention if symptoms occur.

### Most Important Symptoms/Effects, Acute and Delayed (Chronic) Acute Effects

<u>INHALATION:</u> Excessive exposure to high concentrations of dust may cause irritation to the mucous membranes of the upper respiratory tract.

<u>EYE</u>: Excessive exposure to high concentrations of dust may cause irritation to the eyes.

SKIN: Skin contact with dusts may cause irritation or dermatitis.

INGESTION: Ingestion of dust may cause nausea and/or vomiting.

### **Chronic Effects**

Prolonged and repeated inhalation exposure to excessive concentrations of dusts may cause pulmonary fibrosis.



©Roberts Concrete Products (a TCC Materials company) Version 1.2

Immediate Medical Attention and Special Treatment: Treat symptomatically.

## Section 5: Fire Fighting Measures

### Suitable (and Unsuitable) Extinguishing Media

Use extinguishing agents appropriate for surrounding fire.

### **Specific Hazards Arising from the Chemical**

Not applicable for solid product.

### Hazardous combustion products

None known.

### **Special Protective Equipment and Precautions for Firefighters**

Wear full protective firefighting gear including self-contained breathing apparatus (SCBA) for protection against possible exposure to fumes and/or smoke from the fire. Do not release runoff from fire control methods to sewers or waterways.

### Section 6: Accidental Release Measures

### Personal Precautions, Protective Equipment and Emergency Procedures

For spills involving finely divided particles, clean-up personnel should be protected against contact with eyes and skin. If material is in a dry state, avoid inhalation of dust. Fine dry material should be removed by vacuuming or wet sweeping methods to prevent spreading of dust. Avoid use of compressed air to air sweep surfaces. Do not release into sewers or waterways.

### Methods and Materials for Containment and Cleaning Up

Collect spilled material in appropriate, labeled container for recovery or disposal in accordance with federal, state/provincial, and local regulations.

### Section 7: Handling and Storage

### **Precautions for Safe Handling**

Do not breathe dust. Wear protective gloves/clothing and eye/face protection, as applicable. Emergency safety shower and eye wash stations should be present.

### Conditions for Safe Storage, including any Incompatibilities

Store away from incompatibles such as strong acids and bases.



©Roberts Concrete Products (a TCC Materials company) Version 1.2

## Section 8: Exposure Controls/Personal Protection

## **Occupational Exposure Limits:**

	OSHA (US)	OSHA Mexico*	ACGIH	NIOSH
Iron oxide (1309-37-1)	10 mg/m <sup>3</sup> TWA (fume) 15 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> TWA (respirable fraction)	5 mg/m <sup>3</sup> TWA LMPE-PPT 10 mg/m <sup>3</sup> STEL [LMPE- CT] (as Fe)	5 mg/m <sup>3</sup> TWA (respirable factor)	5 mg/m <sup>3</sup> TWA (as Fe, dust and fume)
Amorphous Fused Silicon Dioxide (60676-86-0)	80 mg/m <sup>3</sup> / %SiO₂ TWA			6 mg/m³ TWA
Calcium oxide (1305-78-8)	5 mg/m³ TWA	2 mg/m <sup>3</sup> TWA LMPE- PPT	2 mg/m <sup>3</sup> TWA	2 mg/m <sup>3</sup> TWA 25 mg/m <sup>3</sup> IDLH
Aluminum oxide (1344-28-1)	15 mg/m <sup>3</sup> TWA (total dust) 5 mg/m <sup>3</sup> (respirable fraction)	10 mg/m <sup>3</sup> TWA LMPE-PPT		

## Appropriate Engineering Controls

Local exhaust ventilation should be used to control the emissions of air contaminants below recommended exposure limits. General dilution ventilation may assist with the reductions of air contaminant concentrations. Emergency eye wash stations and deluge safety showers should be available in the work area.

### Individual Protection Measures, such as Personal Protective Equipment Respiratory protection

Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, use only a NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contaminations, and presence of sufficient oxygen. Concentration in air of the various contaminants determines the extent of respiratory protection needed.

Half-face, negative-pressure, air-purifying respirator equipped with P100 filter is



©Roberts Concrete Products (a TCC Materials company) Version 1.2

acceptable for concentrations up to 10 times the exposure limit. Full-face, negative-pressure, air-purifying respirator equipped with P100 filter is acceptable for concentrations up to 50 times the exposure limit. Protection by air-purifying negative-pressure and powered air respirators is limited. Use a positive-pressure-demand, full-face, supplied air respirator or self-contained breathing apparatus (SCBA) for concentrations above 50 times the exposure limit. If exposure is above the IDLH (immediately dangerous to life of health) for any of the constituents, or there is a possibility of an uncontrolled release or exposure levels are unknown, then use a positive-demand, full-face, supplied air respirator with escape bottle or SCBA.

**WARNING!** Air-purifying respirators both negative-pressure, and powered-air do not protect workers in oxygen-deficient atmospheres.

### **Eye/Face protection**

Wear eye protection/face protection. Chemical goggles, face shields, or glasses should be worn to prevent eye contact. Contact lenses should not be worn where particulate exposure to this material is likely.

#### **Skin protection**

Persons handling this product should wear appropriate clothing to prevent skin contact. Take off contaminated clothing and wash before reuse. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves.

Physical State: Appearance: Color: Physical Form: Odor: Odor Threshold: pH: Melting Point: Boiling Point: Boiling Point: Boiling Point: Flash Point: Decomposition: Evaporation Rate: OSHA Flammability Class: LEL: UEL: Vapor Pressure:	Coarse Solid Black, granular shiny solid Black Solid No characteristic odor Not available Not Available Not Available Not Applicable Not Applicable Not Applicable Not Available Not Available Not Available Not Available Not Available Not Available Not Available Not Available Not Available
· · · · · · · · · · · · · · · · · · ·	Page <b>5</b> of <b>10</b>

### **Section 9: Physical and Chemical Properties**



©Roberts Concrete Products (a TCC Materials company) Version 1.2

Vapor Density (air = 1): Density: Specific Gravity (water = 1): Water Solubility: Log KOW: Coeff. Water/Oil Dist: Viscosity: Not Applicable Not Available Not Available Marginal Not Available Not Available Not Available

## **Other Property Information**

No additional information is available.

### Section 10: Stability and Reactivity

### Reactivity

No reactivity hazard is expected.

### Chemical Stability

Coal Slag is stable at normal temperatures and pressure.

### **Possibility of Hazardous Reactions**

None known.

## Conditions to Avoid

Storage with incompatible materials. Flames and ignition sources where dust can accumulate.

#### Incompatible Materials

Strong acids or bases.

### Hazardous Decomposition

Oxides of carbon and metal oxides may be released at elevated temperatures.

### Section 11: Toxicological Information

#### Acute Toxicity Values:

	-	
Coal Slag	Oral LD50 Rat	>2,000 mg/kg
	Dermal LD50 Rabbit	>2,000 mg/kg
Iron Oxide	Oral LD50 Rat	>10,000 mg/kg
Amorphous Silicon Dioxide	Oral LD50 Rat	>5,000 mg/kg
	Dermal LD50 Rabbit	>2,000 mg/kg
Aluminum Oxide	Oral LD50 Rat	>5,000 mg/kg
Calcium Oxide	Oral LD50 Rat	>2,000 mg/kg

No **Skin (Dermal) Irritation** data has been determined for Coal Slag as a mixture. The following is available for components:

Calcium Oxide and Iron Oxide: Moderately irritating.

No **Eye Irritation** data has been determined for Coal Slag as a mixture or its individual components.



©Roberts Concrete Products (a TCC Materials company) Version 1.2

No **Skin (Dermal)/Respiratory Sensitization** data has been determined for Coal Slag as a mixture or its individual components.

No **Aspiration Hazard** data has been determined for Coal Slag as a mixture or its individual components.

No **Germ Cell Mutangenicity** data has been determined for Coal Slag as a mixture or its individual components.

**Carcinogenicity:** Coal Slag **is no**t listed as a carcinogen by IARC, NTP, NIOSH, and OSHA. The following information was identified for the components:

Iron Oxide: ACGIH A4-Not Classifiable as a Human Carcinogen. Beryllium: NTP and IARC – Know to be a Human Carcinogen. Crystalline Silica: NTP and IARC – Known to be a Human Carcinogen.

No **Toxic Reproductive** data has been determined for Coal Slag as a mixture or its individual components.

No **Specific Target Organ Toxicity (STOT) following Single Exposure** data has been determined for Coal Slag as a mixture. The following information was identified for the components:

Calcium Oxide: Can cause respiratory tract infection, skin and eye irritation.

**Specific Target Organ Toxicity (STOT) following Prolonged or Repeated Exposure** data has been determined for Coal Slag as a mixture. The following information was identified for the components:

Coal Slag: Repeated or prolonged inhalation exposure to excessive concentrations of coal slag can cause lung fibrosis. Iron Oxide: Repeated or prolonged inhalation exposure of excessive

concentrations of iron oxide dust can cause a benign lung disease, called Siderosis.

## Section 12: Ecological Information

## Ecotoxicity (aquatic and terrestrial)

Coal slag is not classified as environmentally hazardous. However, this does not exclude the possibility that large amounts or frequent spills can have a harmful or damaging effect on the environment.

### Persistence and Degradability

No data available for coal slag.

## **Bioaccumulative Potential**

No data available for coal slag.



©Roberts Concrete Products (a TCC Materials company) Version 1.2

## Mobility

No data available for coal slag.

## Section 13: Disposal Considerations

## **Disposal Methods**

Dispose of in accordance with federal, state, and local regulations. Observe safe handling procedures.

## Section 14: Transportation

Coal Slag does not have a Transport Dangerous Goods (TDG) classification.

## US Department of Transportation, DOT (49 CFR 172.101):

Shipping Name: Coal Slag is Not Regulated.

### International Maritime Dangerous Goods (IMDG):

Shipping Name: Coal Slag is Not Regulated.

### Section 15: Regulatory Information

## Component Analysis

## **U.S. Federal Regulations**

Coal Slag contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 311/312 (40 CFR 370.21), SARA Section 313 (40 CFR 372-65), CERCLA (40 CFR 302.4), and TSCA 12(b).

### Aluminum oxide (1344-28-1)

**SARA 313:** 1.0 % de minimis concentration (fibrous forms)

### SARA 311/312 Hazardous Categories

Acute Health: Yes Chronic Health: Yes Fire: No Pressure: No Reactive: No

### U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
Iron oxide	1309-37-1	Yes	Yes	Yes	Yes	Yes
Amorphous Silicon Dioxide	60676-86-0	Yes	Yes	Yes	Yes	Yes
Calcium oxide	1305-78-8	Yes	Yes	Yes	Yes	Yes
Aluminum oxide	1344-28-1	Yes	Yes	Yes	Yes	Yes



©Roberts Concrete Products (a TCC Materials company) Version 1.2

Titanium oxide	13463-67-7	Yes	Yes	No	Yes	Yes
Potassium oxide	12136-45-7	Yes	Yes	No	Yes	Yes
Magnesium oxide	1309-48-4	Yes	Yes	No	Yes	Yes
Sodium oxide	1313-59-3	Yes	Yes	Yes	Yes	Yes

The state of California requires the following statement (Proposition 65) in regards to this material:



WARNING: Cancer - <u>www.P65Warnings.ca.gov</u>

## **Component Analysis - Inventory**

Component	CAS	US	CA	EU	AU	PH	JP	KR	CN	NZ
Iron oxide	1309-37-1	Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	Yes
Amorphous Silicon Dioxide	60676-86-0	Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	Yes
Calcium oxide	1305-78-8	Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	Yes
Aluminum oxide	1344-28-1	Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	Yes
Titanium oxide	13463-67-7	Yes	DSL	EIN	Yes	Yes	No	Yes	Yes	Yes
Potassium oxide	12136-45-7	Yes	DSL	EIN	Yes	Yes	No	Yes	Yes	Yes
Magnesium oxide	1309-48-4	Yes	DSL	EIN	Yes	Yes	No	Yes	Yes	Yes
Sodium oxide	1313-59-3	Yes	DSL	EIN	Yes	Yes	No	Yes	Yes	Yes

### **Section 16: Other Information**

Web Sites with information about health effects from occupational exposure to the chemical substances contained in this product and associated engineering controls and personal protective equipment:

OSHA Website: http://www.osha.gov NIOSH Website: http://www.cdc.gov.niosh ACGIH Website: http://www.acgih.org ATSDR Website: http://astdr.cdc.gov/toxprofiles

Additional information on the products is available at. www.tccmaterials.com

Date of Preparation:	June 4, 2018
Version:	1.2

Roberts Concrete Products  $^{\ensuremath{\text{R}}}$  , a TCC Materials  $^{\ensuremath{\text{R}}}$  company, is a licensed manufacturer of SAKRETE  $^{\ensuremath{\text{R}}}$ 

SAKRETE® is a registered trademark of SAKRETE of North America, LLC.



©Roberts Concrete Products (a TCC Materials company) Version 1.2

**Disclaimer:** We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.