



BLACKTOP REPAIR TUBE

◆ The Pro's Choice Since 1936



Sakrete® BlackTop Repair Tube is a siliconized acrylic latex caulk designed for a flexible and durable seal when filling cracks in blacktop surfaces.

Features:

- No mixing – ready to use right from the tube using a standard caulk gun
- Weather resistant after curing
- Convenient for small repairs.

Use For:

- Repairing cracks from 1/8" (3.2 mm) to 3/8" (9.5 mm) in blacktop surfaces

Yield/Coverage:

Container Size	Yield
10.3 fl oz (304 mL) BOM 120040	Will fill cracks approximately 1/4" (6.3 mm) x 1/4" (6.3 mm) by 25' (7.6 m) long

NOTE: The yield is approximate and does not allow for waste and spillage.

Technical Data:

DIVISION 32

Flexible Pavement Repair – 32 01 17

Color:

Black

Preparation:

For best results all materials should be stored between 50°F (10°C) and 90°F (32°C) 24 hours prior to installation. Do not allow to freeze.

1. Chisel out loose blacktop.
2. Clean all surfaces before application.
3. Cleaned surfaces may be moist.
4. Backfill deep cracks with sand or foam backer rod to within 3/8" (9.5 mm) of the surface.
5. Very small cracks should be slightly widened to permit penetration of caulk.

Application:

1. Cut the tube nozzle tip to the approximate width of bead desired and puncture seal at the inside base of tip. Squeeze caulk into the crack using a standard caulking gun.

2. Smooth and trim off excess caulk with a moist putty knife or jointing tool while caulk is very fresh also assuring joints or cracks are filled full.
3. Crack surfaces to be caulked, and caulking material must be above 50°F (10°C) and must remain so for 48 - 72 hours after application with no rain in the forecast for proper curing.
4. Temperature and humidity will affect curing time.

Clean up:

1. Cleans up with water prior to drying.

Curing:

Allow to air-cure for 48 - 72 hours prior to traffic

VOC:

<50 g/l

Precautions:

Air, mix and substrate temperatures should be between 50°F (10°C) and 90°F (32°C) and no rain in the forecast within 24 hours of application.

- Colder temperatures or higher humidity conditions will retard set times
- Protect from freezing for 48 hours after application.

NOTE: STORE SAKRETE BLACK TOP CRACK FILLER IN AN AREA THAT WILL PREVENT IT FROM FREEZING

NOTE: Proper application and installation of all Sakrete products are the responsibility of the end user.

Safety:

READ and UNDERSTAND the Safety Data Sheet (SDS) before using this product. WARNING: Wear protective clothing and equipment. For emergency information, call CHEMTREC at 800-424-9300 or 703-527-3887 (outside USA).

KEEP OUT OF REACH OF CHILDREN.

Limited Product Warranty:

The manufacturer warrants that this product shall be of merchantable quality when used or applied in accordance with the manufacturer's instructions. This product is not warranted as suitable for any purpose other than the general purpose for which it is intended. This warranty runs for one (1) year from the dates the product is purchased. ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ON THIS PRODUCT IS LIMITED TO THE DURATION OF THIS WARRANTY. Liability under this warranty is limited to replacement or defective products or, at the manufacturer's option, refund of the purchase price. CONSEQUENTIAL AND INCIDENTAL DAMAGES ARE NOT RECOVERABLE UNDER THIS WARRANTY.