



Trowelable Blacktop Repair

Blacktop crack filler and mastic patch

©TCC Materials • March 2015 • Version 1.0

Product Description

SAKRETE® Trowelable Blacktop Repair can be used directly from the container. Smooth unsightly rough alligatored pavement areas. Adheres tightly to sides of properly prepared cracks and joints to help keep out moisture, reducing pavement break-up caused by freeze-thaw action. For filling and sealing cracks up to 1 in. (25 mm) wide in blacktop and surfaces such as driveways and parking areas. Repairs dips, rough surfaces, and holes in blacktop driveways, and parking areas.

When/Where to Use

- Existing asphalt / blacktop surfaces
- Driveways
- Parking areas
- Repairs dips, rough surfaces, and holes
- May be used prior to seal-coating

Advantages

- Ready to use - no mixing or dilution
- Fills and seals cracks up to 1 in. wide
- Extends the life of pavement areas
- Maintains bond and elasticity through extreme weather conditions
- Extends the useful life of blacktop surfaces

Packaging

1 qt. (.95 L) tub (BOM 120038)

Typical Yield

1 qt. (.95 L) will cover approximately 3 sq. ft. at 1/8 in. (3 mm) thickness

Surface Preparation

Clean all dirt, dust, and loose materials from cracks or rough surfaces with a stiff broom or stream of water. Allow to dry

KEEP FROM FREEZING

WARNING: INJURIOUS TO EYES!

KEEP OUT OF REACH OF CHILDREN!

Helpful Items:



Safety Glasses

Gloves

Broom

Trowel

prior to application of Trowelable Blacktop Repair.

Mixing

No mixing is required, gently stir product before use. Do not dilute with water or solvents.

Application

Read all directions before starting work. For best results, apply in dry, warm weather. Do not apply when rain is forecasted or when the ambient air temperature is expected to fall below 50°F (10°C) within 48 hours. To fill cracks in area to be smoothed, apply Trowelable Blacktop Repair with cement trowel or putty knife by pressing material into crevices to improve bond. Smooth finish patch with damp application tool. For rough textured pavement areas, trowel over surface up to 1/8 in. thick. Thicker applications will require longer curing and may be damaged if rain occurs before surface cures. (Do not apply in cracks over 1 in. wide or on surfaces over 1/8 in. thick).

Clean up

Use warm, soapy water for cleaning hands while product is wet. Dried Trowelable Blacktop Repair is insoluble in water. Clean tools and spills before it dries. Hardened product remaining on tools may be removed with mineral spirits.

Curing

Allow Trowelable Blacktop Repair to cure 48 hours before seal-coating. Curing time will vary with thickness of application. Surface will usually cure in 48 hours but weather and thickness may slow drying. Curing to full depth of cracks may take 5 to 7 days. Keep traffic off the repair area if possible during the curing period. If this cannot be done, sprinkle sand over the repair area to prevent tracking.

Notes and Limitations:

- Rubber gloves and goggles are

recommended safety equipment

- Store in tightly sealed original factory containers off the floor in a dry place
- Do not apply in cracks over 1 in. wide or on surfaces over 1/8 in. thick

Proper application and installation of all SAKRETE products are the responsibility of the end user.

Warning

WARNING! CAUSES IRRITATION - Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Exposure may result in irritation of the skin.

FIRST AID: In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get prompt medical attention; for skin, washing thoroughly with plenty of soap and water. If irritation persists, get medical attention. **KEEP OUT OF REACH OF CHILDREN.** READ and UNDERSTAND the Safety Data Sheet (SDS) before using this product.



Limited Product Warranty

The manufacturer warrants that this product shall be of merchantable quality when used or applied in accordance with the manufacturer's instructions. This product is not warranted as suitable for any purpose other than the general purpose for which it is intended. This warranty runs for one (1) year from the dates the product is purchased. ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ON THIS PRODUCT IS LIMITED TO THE DURATION OF THIS WARRANTY. Liability under this warranty is limited to replacement of defective products or, at the manufacturer's option, refund of the purchase price. **CONSEQUENTIAL AND INCIDENTAL DAMAGES ARE NOT RECOVERABLE UNDER THIS WARRANTY.**

SAKRETE® and the background design are registered trademarks of SAKRETE of North America LLC, Charlotte, NC 28273 • ©2006. SAKRETE® is manufactured under license from SAKRETE of North America LLC.

Shelf Life	One year in original, unopened container.
Storage Conditions	Store dry in tightly sealed original container.
Color	Black.