

1. Identification	
Product identifier	
Product name	Athletic Field Marker
CAS number	1317-65-3
Molecular Weight	100.1 g/mol
Details of the supplier of the sa	afety data sheet
Supplier	Imerys Carbonates USA, Inc. 100 Mansell Court East, Ste 300 Roswell Georgia 30076, USA +1 770 594-0660 +1 770 645-3384
Manufacturer	Imerys Carbonates USA, Inc. 10000 Beaver Dam Road Cockeysville, MD 21030
Emergency telephone number	
National emergency telephone number	+1 (800) 424-9300 CHEMTREC
2. Hazard(s) identification	
Classification of the substance	e or mixture
OSHA Regulatory Status	This Product is Hazardous under the OSHA Hazard Communication Standard.
Physical hazards	Not Classified
Health hazards	STOT RE 1 - H372
Environmental hazards	Not Classified
Human health	Long term exposure to crystalline silica can cause lung injury (silicosis). IARC and NTP have determined that crystalline silica inhaled from occupational sources can cause cancer in humans. Risk of injury is dependent on the duration and level of exposure.
Label elements	
Pictogram	
Signal word	Danger
Hazard statements	H372 Causes damage to organs through prolonged or repeated exposure.

Precautionary statements	 P260 Do not breathe dust. P264 Wash contaminated skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P314 Get medical advice/ attention if you feel unwell. P501 Dispose of contents/ container in accordance with national regulations.
Contains	Quartz
3. Composition/information on	ingredients
Substances	
Ground Limestone (Calcium Carbonate) >97%	
CAS number: 1317-65-3	
Classification Not Classified	
Quartz CAS number: 14808-60-7	~3%
CAS number. 14008-00-7	
Classification STOT RE 1 - H372	
Water	<0.5%
CAS number: 7732-18-5	
Classification Not Classified	
The full text for all hazard state	ements is displayed in Section 16.
Product name	Athletic Field Marker
CAS number	1317-65-3
4. First-aid measures	
Description of first aid measur	es
Inhalation	Move affected person to fresh air at once.
Ingestion	Rinse mouth thoroughly with water. Give plenty of water to drink. Never give anything by mouth to an unconscious person.
Skin Contact	Wash with plenty of soap and water.
Eye contact	Rinse cautiously with water for several minutes.
Most important symptoms and	l effects, both acute and delayed
General information	The product is considered to be a low hazard under normal conditions of use.
5. Fire-fighting measures	
Extinguishing media	
Suitable extinguishing media	The product is non-combustible

Suitable extinguishing media The product is non-combustible.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions	Use proper respiratory and personal protective equipment. MSHA / NIOSH or OSHA / NIOSH approved respirator recommended. Spilled materials may cause slippery conditions when wet. Care should be exercised when walking on spills on floors or concrete pads.
Methods and material for cont	ainment and cleaning up
Methods for cleaning up	Vacuum, pump or scoop spilled material into containers for reclaiming or disposal. Do not discharge into drains, watercourses or onto the ground.
7. Handling and storage	
Precautions for safe handling	
Usage precautions	Avoid handling which leads to dust formation. Observe occupational exposure limits and minimise the risk of inhalation of dust.
Conditions for safe storage, in	cluding any incompatibilities
Storage precautions	Store in a cool and well-ventilated place. Store away from acids.
8. Exposure Controls/persona	I protection
Control parameters Occupational exposure limits	
• • •	our TWA): OSHA 5 mg/m³ respirable fraction our TWA): OSHA 15 mg/m³ total dust
Ground Limestone (Calcium C	arbonate)
• • •	our TWA): OSHA 5 mg/m³ respirable fraction our TWA): OSHA 15 mg/m³ total dust
Quartz	
• • •	our TWA): OSHA 0.05 mg/m³ respirable dust our TWA): ACGIH 0.025 mg/m³ respirable fraction
OSHA = Occupational Safety ACGIH = American Conference A2 = Suspected Human Carci	ce of Governmental Industrial Hygienists.
	Quartz (CAS: 14808-60-7)
Ingredient comm	Long term exposure to crystalline silica can cause lung injury (silicosis). IARC and NTP have determined that crystalline silica inhaled from occupational sources can cause cancer in humans. Risk of injury is dependent on the duration and level of exposure.
Exposure controls	
Appropriate engineering controls	Provide adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Observe any occupational exposure limits for the product or ingredients.
Eye/face protection	Wear safety glasses with side-shields in circumstances where there is a risk of penetrative

eye injuries.

Hand protectionFor prolonged or repeated skin contact use suitable protective gloves.

Hygiene measures Wash hands thoroughly after handling. Use appropriate skin cream to prevent drying of skin.

Respiratory protection	Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.
Immediate danger to life and health	25 mg/m³
9. Physical and Chemical Prop	perties
Information on basic physical	and chemical properties
Appearance	Powder
Color	White.
Odor	Odorless.
рН	8-9
Initial boiling point and range	Not applicable.
Flash point	Not applicable.
Upper/lower flammability or explosive limits	Not applicable.
Solubility(ies)	Slightly soluble in water.
Auto-ignition temperature	Not applicable.
Decomposition Temperature	825°C/1517°F
Refractive index	1.6
Molecular weight	100.1
10. Stability and reactivity	
Reactivity	Acids.
Stability	No particular stability concerns. Will decompose at temperatures exceeding 825°C.
Conditions to avoid	Acids. Avoid handling which leads to dust formation.

Materials to avoid Acids.

Hazardous decomposition Carbon dioxide (CO2). products

Acute toxicity - oral	
Notes (oral LD₅₀)	Quartz: 6450 mg/kg (rat)
Skin corrosion/irritation	
Skin corrosion/irritation	Prolonged contact may cause dryness of the skin.
Carcinogenicity	
IARC carcinogenicity	IARC Group 1 Carcinogenic to humans.
NTP carcinogenicity	Known human carcinogen.

STOT - repeated exposure	Long term exposure to crystalline silica can cause lung injury (silicosis). IARC and NTP have determined that crystalline silica inhaled from occupational exposure sources can cause cancer in humans. Risk of injury is dependent on duration and level of exposure.
Target organs	Lungs
12. Ecological Information	
Ecotoxicity	The product is not expected to be hazardous to the environment.
13. Disposal considerations	
Waste treatment methods	
Disposal methods	Under RCRA (40 CFR 261) ground limestone is a non-hazardous waste. Dispose of waste materials in accordance with all local, state and federal requirements.
14. Transport information	
General	No special precautions.
Environmental hazards	
Environmentally Hazardous S No.	Substance
15. Regulatory information	
US Federal Regulations SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities Not listed. CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA) Not listed.	
SARA 313 Emission Reporting Not listed.	
SARA (311/312) Hazard Categories Immediate Delayed	
US State Regulations California Proposition 65 Carcinogens and Reproductive Toxins This product contains Crystalline Silica (quartz), which in its respirable form, is known to the state of California to cause cancer and/or birth defects and other reproductive harm.	
Massachusetts "Right To Know" List Present.	
Rhode Island "Right To Know Present.	/" List
Minnesota "Right To Know" L Present.	ist
New Jersey "Right To Know" Present.	List

Pennsylvania "Right To Know" List Present.

Inventories

EU - EINECS/ELINCS Yes

Canada - DSL/NDSL Yes

US - TSCA Yes

US - TSCA 12(b) Export Notification No.

Australia - AICS Yes

Japan - MITI Yes

Korea - KECI Yes

China - IECSC Yes

Philippines - PICCS Yes

New Zealand - NZIOC Yes

Taiwan - NECI Yes

16. Other information

Abbreviations and acronyms used in the safety data sheet	CFR: Code of Federal Regulation IARC: International Agency for Research on Cancer MSHA: Mine Safety and Health Administration NIOSH: National Institute for Occupational Safety and Health NTP: National Toxicology Program OSHA: Occupational Safety and Health Administration RCRA: Resource Conservation and Recovery Act TWA: Time Weighted Average
Classification abbreviations and acronyms	STOT RE = Specific target organ toxicity-repeated exposure
Revision date	4/2/2018
SDS No.	22667
WHMIS	Ground limestone containing more than 0.1% of a carcinogenic substance (crystalline silica) is classified as carcinogenicity - Category 1A.

Hazard statements in full	H372 Causes damage to organs through prolonged or repeated exposure. H372 Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled.
ACA HMIS Health rating.	Slight Hazard. (1)
ACA HMIS Flammability rating.	Will not burn. (0)
ACA HMIS Physical hazard rating.	Normally stable. (0)
ACA HMIS Personal protection rating.	E

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.