

	GRAY POURABLE CONCRETE CRACK FILLER	CONCRETE REPAIR	MORTAR REPAIR	AKONASEAL® NON-SAG MASONRY/Joint SEALANT	AKONAFLEX® SELF-LEVELING CONCRETE REPAIR	AKONAFLEX® PRO SELF-LEVELING EXPANSION JOINT FILLER	EPOXY CRACK REPAIR
							
USES & ADVANTAGES	- Economical acrylic - Width: ¼" max - Depth: ¼" max	- Masonry texture - Skims in 24 hours - Durable - Paintable (latex) - Width: ¾" max - Depth: ¾" max	- Textured finish - Skims in 24 hours - Durable - Paintable (latex) - Width: ¾" max - Depth: ¾" max	- Textured, water-resistant - Skims in 24 hours - Flexible - Paintable (latex) - Width: 1" max - Depth: ½" max	- Smooth, water-resistant - Self-leveling (no tooling) - Flexible - Paintable (latex) - Width: 1½" max - Depth: 1" max	- Smooth, water-resistant - Self-leveling (no tooling) - Flexible - Paintable (latex) - Width: 2½" max - Depth: 1½" max	- Smooth finish - High-strength epoxy - Low-viscosity - Moisture tolerant - Width: ¼" max - Depth: 6" max
COVERAGE	1 qt. bottle fills 40 lin. ft. at ¼" deep x ¼" wide 1 gal. bottle fills 160 lin. ft. at ¼" deep x ¼" wide	10.1 oz. tube fills 10 lin. ft. at a ¾"x¾" joint	10.1 oz. tube fills 10 lin. ft. at a ¾"x¾" joint	10.1 oz. tube fills 12 lin. ft. at a ½"x¼" joint	10.1 oz. tube fills 12 lin. ft. at a ½"x¼" joint 29 oz. tube fills 34 lin. ft. at a ½"x¼" joint	10.1 oz. tube fills 12 lin. ft. at a ½"x¼" joint 29 oz. tube fills 34 lin. ft. at a ½"x¼" joint	Net 6 fl. oz. tube will yield approx. 10-11 cu. in.
APPLICATION							
Interior & Exterior	X	X	X	X	X	X	X
Wide or Expansion Joints				X	X	X	
Narrow Holes & Cracks	X	X	X				X
Water-Resistant	X	X	X	X	X	X	X
Vertical Applications		X	X	X			
Horizontal Applications	X	X	X	X	X	X	X
For Mortar, Stucco, Stone			X	X			
For Concrete Surfaces	X	X		X	X	X	X
Paintable	X	X	X	X	X	X	
VOC Compliant	X	X	X	X	X	X	
Available In 2 Sizes	X				X	X	