







| | FLOOR APPLICATIONS | | | WALL APPLICATIONS | | |
|---------------------------------------|--|---|---|---|--|---|
| | POLYMER-MODIFIED CONCRETE RESURFACER | SELF-LEVELING FLOOR UNDERLAYMENT CEMENT | AKONAKOTE® POURABLE CONCRETE PATCH | FOUNDATION COATING CEMENT | CRACK-RESISTANT SURFACE BONDING CEMENT | HEAVY-DUTY WATERPROOFING BASE COAT |
| |  |  |  |  |  |  |
| USES & ADVANTAGES | <ul style="list-style-type: none"> • Renews concrete surfaces • For use on steps, patios, garage floors, and more • Ideal for resurfacing spalled concrete • Polymer-modified • Trowel or broom finish • Designed for even application ¼" thick down to ⅛" | <ul style="list-style-type: none"> • Prepares plywood or concrete surfaces prior to installation of flooring • High-strength • Self-leveling and flow-able mixture • Premixed with integral primer no additional primer required • Provides flat and level floors • Great to encapsulate radiant heat installations | <ul style="list-style-type: none"> • Polymer-modified for superior adhesion • Flowable and pourable • Trowel or stiff-edge blade applied • Corrects defects in concrete surfaces up to ½" prior to applying new floor coverings • Wearable surface up to light-duty commercial | <ul style="list-style-type: none"> • Protects exposed insulation board (ICF) from damage of UV radiation, weathering, or general wear • Polymer-modified and fiber reinforced for superior performance • Easy brush-on or troweled application • Creates textured finish coat of insulation | <ul style="list-style-type: none"> • Bonds dry stacked masonry walls • Glass fiber reinforced for strength & durability • Controls shrinkage, cracking, and sagging on vertical repairs • Repairs deteriorated concrete walls • Patches deep vertical holes in concrete and masonry walls | <ul style="list-style-type: none"> • Waterproof finish coat when mixed with bonding additive and applied in 2-coats • Applies to smooth or textured finishes • Used as a decorative coating • May be painted or faux finished • Used above or below grade • Works on non-uniform surfaces |
| COVERAGE | • 25 lb. yields 25 sq. ft. at ¼" thickness | • 50 lb. yields 50 sq. ft. at ⅛" thickness | • 50 lb. yields 50 sq. ft. at ⅛" thickness | • 50 lb. yields 50 sq. ft. at ⅛" thickness | • 50 lb. yields 50 sq. ft. at ⅛" thickness | • 50 lb. yields 50 sq. ft. at ⅛" thickness |
| APPLICATION | WEARABLE SURFACE | UNDERLAYMENT | WEARABLE SURFACE | WEARABLE SURFACE | WEARABLE SURFACE | WEARABLE SURFACE |
| Interior & Exterior | X | | X | X | X | X |
| Pre-Blended Mixing Liquid: | Water Only | Water Only | Water Only | Water Only | Water or Bonding Additive | Bonding Additive |
| Polymer-Modified | X | X | X | X | | |
| Corrects Defects in Concrete Surfaces | X | X | X | | X | |
| Creates Textured Finish | | | | X | | X |
| Creates Flat Surface | | X | | | | |
| Creates Moisture Resistant Finish | | | | | | X |
| High Strength | | X | | | X | |
| Coating Insulated Concrete Forms | | | | X | | |