








| | MEDIUM-DUTY REFRACTORY MORTAR | NON-SHRINK GROUT | WHITE GLASS BLOCK MORTAR | INSTANT POST CEMENT | INSTANT ANCHORING CEMENT | FAST-SETTING ANCHORING EPOXY | INSTANT WATER STOP |
|--|--|--|--|--|---|--|---|
| |  |  |  |  |  |  |  |
| USES & ADVANTAGES | <ul style="list-style-type: none"> For fireplaces, fire pits, flues, etc. Good for applications up to 2550°F Air entrained for freeze-thaw resistance One hour working time ASTM C199 | <ul style="list-style-type: none"> Capable of handling high load transfers MN DOT approved Non-Shrink Grouts ASTM C1107 Corps of engineers spec. CRD-C 621 | <ul style="list-style-type: none"> For use with glass block in shower or bathroom walls High-strength white mortar Minimizes joint shrinkage Mix with bonding additive for exterior applications | <ul style="list-style-type: none"> Sets fence posts, mailboxes, basketball poles, and swing sets No mixing required No bracing required Fast-setting Not for structural supports (footings) | <ul style="list-style-type: none"> Expands as it hardens Sets handrails, bolts, poles, and fixtures Use with concrete or masonry Sets in 20 minutes | <ul style="list-style-type: none"> High-strength Resists chemicals and solvents Moisture tolerant 100% solids Fast-setting Non-sag | <ul style="list-style-type: none"> Bonds well to wet walls Sets in just 3-5 minutes Plugs holes in walls Seals water flow in basements Great for swimming pool repairs |
| COVERAGE | <ul style="list-style-type: none"> 50 lb. bag yields .5 cu. ft. of wet mortar Will lay 80-100 standard fire bricks at 1/8" joint thickness | <ul style="list-style-type: none"> 50 lb. bag yields 0.45 cu. ft., at a flowable consistency of wet mortar | <ul style="list-style-type: none"> 50 lb. bag yields .5 cu. ft. of wet mortar | <ul style="list-style-type: none"> 50 lb. bag will set a 3" post in a 6" diameter hole with a depth of 24" | <ul style="list-style-type: none"> 10 lb. yields 170 cu. in. or anchors 2 fixtures in a 2" diameter hole with a depth of 2 " | <ul style="list-style-type: none"> 8.45 fl. oz. tube yields 30 lin. ft. at a 1/8" x 1/8" line | <ul style="list-style-type: none"> 10 lb. yields 18 cu. in. or a crack 1" deep by 1/4" wide and 6' long 25 lb. yields 45 cu. in. or a crack 1" deep by 1/4" wide and 15' long |
| APPLICATION | | | | | | | |
| Interior & Exterior | X | X | X | X | X | X | X |
| Pre-Blended: Just Add Water | X | X | X | X | X | Ready to Use | X |
| Fast-Setting | | | | X | X | X | X |
| Setting Fireplace Masonry Units | X | | | | | | |
| Setting Glass Block | | | X | | | | |
| Lead Transfer & Base Weight Distribution | | X | | | | | |
| Setting Large Fixtures (6-12" diameter hole) | | | | X | | | |
| Setting Small Fixtures (2-6" diameter hole) | | X | | | X | X | |
| High Strength/Bond | X | X | X | X | X | X | X |
| Expands As It Sets | | | | | X | | X |
| Low/Non-Shrink | | X | X | | | X | |