

PELLETIZED GYPSUM

Loosener for compacted clay and soils

1. PRODUCT NAME

Pelletized Gypsum

2. MANUFACTURER

MK Minerals Inc.
1035 Vernon Road
Wathena, KS 66090 USA
Phone: 1.785.989.4566

3. PRODUCT DESCRIPTION

Pelletized gypsum helps loosen compacted clay soils and to supply calcium and sulfur to plants. The all-natural formula is safe for the environment and helps to repair damage that has been caused to the turf by road salt and animal burns. Pelletized gypsum uses a fast release formula designated for all-season use.

Features and Benefits

- Suitable for use on new and established lawns
- Covers up to 25 sq. ft.
- Lasts for up to 26 weeks
- Fast-release formula is designed for all-season use
- Provides sulfur and calcium to plants and helps to repair turf damage
- All natural and safe for the environment
- Excellent source of calcium and sulfur
- Improves soil structure which in turn leads to better water and oxygen penetration
- Addresses salt damage from winter de-icing, pets, effluent water and other irrigation/precipitation sources
- Stimulates microorganism growth and helps alleviate blossom end rot
- pH neutral product will not raise soil pH
- Improved plant growth
- Consistent results
- Spread with any fertilizer spreader.

4. TECHNICAL DATA

Available Size

- 40 lb.(18.1 kg) bag (BOM #103589)

5. INSTALLATION

Preparation and Application

Read all directions before starting work. A soil test is recommended whenever possible. When a soil test is not available, follow these recommendations.

Note: It is the responsibility of the installer/applicator to ensure the suitability of the product for its intended use.

Established Lawns: Apply 40-50 lb. Per 1,000 sq. ft. annually in the spring and fall. Water thoroughly.

New Turf: Apply 800-100 lb. per 1,000 sq. ft. annually in the spring and fall. Water thoroughly.

Shrubs, Gardens and Flowers: Incorporate into top 2" of soil, using 2-4 cups around plant base. Water thoroughly.

Corrective Application: Apply 40-50 lb. per 100 sq. ft. Water thoroughly.

Approximate Spreader Settings (per 1,000 sq. ft.)

	20 lb.	40 lb.
Cyclone/Spyker	6	8
Scotts AccuGreen 3000	8	11
Scotts Speedy Green 3000	8	11
Precision Drop	6	10

Clean Up

Use soapy water to clean hands and tools immediately after use.

Safety

READ THE SAFETY DATA SHEET (SDS) BEFORE USING THIS PRODUCT. SDS information is available on our website: tccmaterials.com

Cautions

Read complete cautionary information printed on product container prior to use. This Product Data Sheet has been prepared in good faith on the basis of information available at the time of publication. It is intended to provide users with information about and guidelines for the proper use and application of the product(s) under normal environmental and working conditions. Because each project is different, TCC Materials cannot be responsible for the consequences of variations in such conditions, or for unforeseen conditions.

6. AVAILABILITY

To locate TCC Materials products in your area, please contact:
Phone: 1.651.688.9116
Website: tccmaterials.com

7. WARRANTY

Seller warrants that its product will conform to and perform in accordance with the product specifications. The foregoing warranty is in lieu of all other warranties, expressed or implied, including, but not limited to those concerning merchantability and fitness for a particular purpose. Because of the difficulty in ascertaining and measuring damages hereunder, it is agreed that, Seller's liability to the Buyer shall not exceed the total amount billed and billable to the Buyer for the product hereunder.

WARNING: INJURIOUS TO EYES

KEEP PLASTIC BAG OUT OF REACH OF CHILDREN