



WHITE PORTLAND CEMENT TYPE I

Durable, dependable, cost-effective basic building material

1. PRODUCT NAME

Tech-Mix® White Portland Cement (Type I)

2. MANUFACTURER

Tech-Mix® is a registered trademark of TCC Materials
2025 Centre Pointe Blvd., Suite 300
Mendota Heights, MN 55120 USA
Phone: 1.651.688.9116
Web: techmixpro.com

3. PRODUCT DESCRIPTION

Tech-Mix® White Portland Cement Type I are regularly used to produce architectural concrete. General applications include cast-in-place or precast wall panels, floors, slabs, terrazzo, thin-set and tile grouts, cast stone, masonry units and mortars, stucco, swimming pools & spas, glass fiber reinforced concrete, ornamental statuary, floor tiles, concrete roof tiles, perimeter security, pavers and traffic safety items such as concrete median barriers, bridge parapets, pedestrian crosswalks, curbs and other delineators. White cement is often used to produce bright finishes, vibrant colors or ultra high performance concretes that look great and provide structural performance that make them ideal for resilient building applications.

Features and Benefits

- Durable
- Cost effective
- High strength
- Meets or exceeds ASTM C-150

When/Where to Use

- Precast wall panels
- Floors & slabs
- Terrazzo
- Thin-set and tile grouts
- Cast stone masonry units
- Swimming pools and spas
- Bridges
- Crosswalks
- Curbs

4. TECHNICAL DATA

Meets or exceeds the requirements of ASTM C-150, AASHTO M85 and CSA A3001.

Available Size

- 92.6 lb. (42 kg) bag (BOM #112770)

Coverage

- Each 92.6 lb. bag contains 1 cu. ft.

5. INSTALLATION

Preparation

Read all directions before starting work.

Note: It is the responsibility of the installer/applicator to ensure the suitability of the product for its intended use.

Mixing

Refer to the mix designs chart for typical proportions by volume per appropriate application. Add the minimum amount of clean water necessary, too much water will weaken the product. Mix until uniform, workable consistency is reached.

Typical Mix Designs by Volume		
Concrete Mix		
Portland Cement	General Purpose Sand (ASTM C-33)	Gravel or Stone (ASTM C-33)
1 Part	2 Parts	3 Parts
Mortar Mix (Type S, ASTM C-270)		
Portland Cement	Hydrated Lime Type S	Masonry Sand (ASTM C-144)
1 Part	½ Part	3½ - 4½ Parts
Stucco Mix (Scratch & Brown ASTM C-926)		
Portland Cement	Hydrated Lime Type S	Washed Plaster Sand (ASTM C-897)
1 Part	½ Part	4½ - 6 Parts

Application

Concrete will remain workable for at least 1 hour. The air, mix, and substrate temperatures should all be between 40°-90°F (4.4°-32.2°C). Protect from freezing for at least 48 hours

Curing

To aid curing, spray surface lightly with water 2-3 times per day for 3 days.

Clean Up

Use soapy water to clean hands and tools immediately after use. Dried material must be mechanically removed. Use a waste water hardener (e.g. Congelz™ or similar product) for cementitious waste disposal.

Limitations

- Use only clean mixing container and tools.
- Follow all industry standard safety procedures when working with concrete products including wearing impervious gloves, such as nitrile when handling.
- Portland Cement mixes should be installed in accordance with local building code provisions and all applicable ASTM standards.

Safety

READ THE SAFETY DATA SHEET (SDS) BEFORE USING THIS PRODUCT. SDS information is available on our website: techmixpro.com

Cautions

Read complete cautionary information printed on product container prior to use. This Product Data Sheet has been prepared in good faith on the basis of information available at the time of publication. It is intended to provide users with information about and guidelines for the proper use and application of the covered Tech-Mix brand product(s) under normal environmental and working conditions. Because each project is different, TCC Materials cannot be responsible for the consequences of variations in such conditions, or for unforeseen conditions.

6. AVAILABILITY

To locate Tech-Mix products in your area, please contact:

Phone: 1.651.688.9116

Website: techmixpro.com

7. WARRANTY

Seller warrants that its product will conform to and perform in accordance with the product specifications. The foregoing warranty is in lieu of all other warranties, expressed or implied, including, but not limited to those concerning merchantability and fitness for a particular purpose. Because of the difficulty in ascertaining and measuring damages hereunder, it is agreed that Seller's liability to the Buyer shall not exceed the total amount billed and billable to the Buyer for the product hereunder.

Shelf Life	Best when used within one year in original, unopened bags
Storage Conditions	Store dry, cool, in tightly closed container.
Color	Gray

WARNING: INJURIOUS TO EYES

KEEP OUT OF REACH OF CHILDREN



Tech-Mix® is a registered trademark of TCC Materials
2025 Centre Pointe Blvd., Suite 300
Mendota Heights, MN 55120 USA
www.techmixpro.com
©Copyright 2020 TCC Materials

REV 02/20