

BLUESTONE PRODUCTS™
A TCC Materials Company
2025 Centre Pointe Boulevard
Mendota Heights, MN 55120-1221

Emergency Telephone Number:
651-688-9116
Information Telephone Number
651-905-8137

Revision Date
April 2021

Section 1: Product Identification

Product Type: Adhesive, Sealant

Product Name:

ProSpec[®] Stone Veneer Sealant - Charcoal

Section 2: Hazard Identification

Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

Acute Toxicity - Oral - Category 4

Serious Eye Damage/Eye Irritation - Category 2A

Carcinogenicity - Category 1A

Reproductive Toxicity - Category 1B

Specific Target Organ Toxicity - Single Exposure - Category 1 (central nervous system)

Specific Target Organ Toxicity - Repeated Exposure - Category 1 (respiratory system)

Specific Target Organ Toxicity - Repeated Exposure - Category 2 (bladder)

GHS Label Elements

Symbol(s)



Signal Word

Danger

Hazard Statement(s)

Harmful if swallowed.

Causes serious eye irritation.

May cause cancer.

May damage fertility or the unborn child.

Causes damage to organs.

Causes damage to organs through prolonged or repeated exposure.

May cause damage to organs through prolonged or repeated exposure.

Precautionary Statement(s)

Prevention

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Wear eye protection/face protection.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.

Response

If exposed: Call a POISON CENTER or doctor/physician.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.
IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
Rinse mouth.
Get medical advice/attention if you feel unwell.
Specific treatment (see label).

Storage

Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Statement(s) of Unknown Acute Toxicity

Oral 71.91% of the mixture consists of ingredient(s) of unknown acute toxicity.

Section 3: Hazardous Ingredients/Composition

Ingredient	Typical Percentage	CAS #
Calcium Carbonate.....	10-25%	1317-65-3
Carbonic acid, calcium salt (1:1)	15-40%	471-34-1
Titanium dioxide (white, gray, beige and neutral).....	1-5%	13463-67-7
Organosilane.....	1-5%	2768-02-7
Dibutyltin oxide.....	0.1-1	818-08-6
Diisononyl Phthalate.....	15-35%	28553-12-0
Carbon black (black, bronze, gray).....	0.01-1	1333-86-4

Section 4: First Aid Measures

Inhalation:

IF INHALED: If breathing is difficult, remove person to fresh air and keep at rest in a position comfortable for breathing Call a POISON CENTER or doctor/physician if you feel unwell.

Eye contact:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention

Skin Contact:

IF ON SKIN Wash with plenty of soap and water If skin irritation or rash occurs: Get medical advice/attention Take off contaminated clothing and wash before reuse

Ingestion:

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting

Most Important Symptoms/Effects (Acute and Delayed)

Acute

Harmful if swallowed. Causes serious eye irritation.

Delayed

May cause cancer. May damage fertility or the unborn child. Causes damage to organs. Causes damage to organs through prolonged or repeated exposure.

Section 5: Fire Fighting Measures

Extinguishing Media

Suitable Extinguishing Media

Use carbon dioxide, regular dry chemical, regular foam or water.

Unsuitable Extinguishing Media

Do not use high-pressure water streams.

Special Hazards Arising from the Chemical

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

Hazardous Combustion Products

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

Advice for firefighters

Heating may cause an explosion. Containers may rupture or explode.

Fire Fighting Measures

Keep away from sources of ignition - No smoking Move material from fire area if it can be done without risk Avoid inhalation of vapors or combustion by-products. Dike for later disposal. Stay upwind and keep out of low areas.

Special Protective Equipment and Precautions for Firefighters

A positive-pressure, self-contained breathing apparatus (SCBA) and full-body protective equipment are required for fire emergencies.

Section 6: Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8.

Methods and Materials for Containment and Cleaning Up

Keep unnecessary people away, isolate hazard area and deny entry. In case of spillage, stop the flow of material and block any potential routes to water systems. Only personnel trained for the hazards of this material should perform clean up and disposal.

Environmental Precautions

Do not flush into sanitary sewer systems, drains or surface water. Avoid release to the environment.

Section 7: Handling and Storage

Precautions for Safe Handling

Do not handle until all safety precautions have been read and understood. Keep away from all ignition sources. Avoid contact with eyes and skin. Do not eat, drink or smoke when using this product. Always wear recommended personal protective equipment. Wear personal protective clothing and equipment, see Section 8. Take precautionary measures against static discharge.

Conditions for Safe Storage, Including any Incompatibilities

Store locked up.

Store in a cool dry place. Store in a well-ventilated area. Keep separated from incompatible substances. Keep container tightly closed. Empty containers may contain product residue. Store and handle in accordance with all current regulations and standards. Avoid contact with temperatures above 120 C.

Incompatible Materials

Strong oxidizer. Strong acids.

Section 8: Exposure Controls/Personal Protection

Component Exposure Limits:

Calcium carbonate	1317-65-3
NIOSH:	10 mg/m ³ TWA total dust ; 5 mg/m ³ TWA respirable dust
OSHA (US):	15 mg/m ³ TWA total dust ; 5 mg/m ³ TWA respirable fraction
Mexico:	10 mg/m ³ TWA VLE-PPT
	20 mg/m ³ STEL [PPT-CT]
Carbonic acid, calcium salt (1:1)	471-34-1
NIOSH:	10 mg/m ³ TWA total dust ; 5 mg/m ³ TWA respirable dust
Titanium dioxide	13463-67-7
ACGIH:	10 mg/m ³ TWA
NIOSH:	2.4 mg/m ³ TWA (CIB 63) fine ; 0.3 mg/m ³ TWA (CIB 63) ultrafine, including engineered nanoscale
	5000 mg/m ³ IDLH
OSHA (US):	15 mg/m ³ TWA total dust
Mexico:	10 mg/m ³ TWA VLE-PPT as Ti
	20 mg/m ³ STEL [PPT-CT] as Ti
Carbon black	1333-86-4
ACGIH:	3 mg/m ³ TWA inhalable particulate matter
NIOSH:	3.5 mg/m ³ TWA ; 0.1 mg/m ³ TWA (Carbon black in presence of Polycyclic aromatic hydrocarbons) as PAH
	1750 mg/m ³ IDLH
OSHA (US):	3.5 mg/m ³ TWA
Mexico:	3.5 mg/m ³ TWA VLE-PPT
	7 mg/m ³ STEL [PPT-CT]

ACGIH - Threshold Limit Values - Biological Exposure Indices (BEI)

There are no biological limit values for any of this product's components.

Engineering Controls:

Ventilation equipment should be explosion-resistant if explosive concentrations of material are present. Provide local exhaust or process enclosure ventilation system.

Personal protective equipment: Wear appropriate chemical resistant clothing.

Face and eyes: Wear splash resistant safety goggles with a faceshield.

Body: Avoid any skin contact, particularly when skin may be wet from sweat. Long sleeved shirts and trousers should be worn while using this material. Wear any water-impermeable gloves such as PVC gloves, particularly for prolonged contact. Wear

waterproof boots, high enough to prevent any cement from getting into them. Promptly wash off of skin and remove contaminated clothing.

Respiratory: Selection and use of respiratory protective equipment should be in accordance in the USA with OSHA General Industry Standard 29 CFR 1910.134; or in Canada with CSA Standard Z94.4.

Hands: Wear appropriate chemical resistant gloves.

Section 9: Physical and Chemical Properties

Appearance	Paste	Physical State	Solid
Odor	Mild	Color	Black , white , other
Odor Threshold	Not available	pH	Not available
Melting Point	Not available	Boiling Point	Not available
Boiling Point Range	Not available	Freezing point	Not available
Evaporation Rate	Not available	Flammability (solid, gas)	Not available
Autoignition Temperature	Not available	Flash Point	93.3 °C (>200 °F)
Lower Explosive Limit	Not available	Decomposition temperature	Not available
Upper Explosive Limit	Not available	Vapor Pressure	Not available
Vapor Density (air=1)	Not available	Specific Gravity (water=1)	1.3 - 1.7
Water Solubility	(Slightly soluble)	Partition coefficient: n-octanol/water	Not available
Viscosity	Not available	Kinematic viscosity	Not available
Solubility (Other)	Not available	Density	Not available
Physical Form	Paste	Molecular Weight	Not available

Section 10: Stability and Reactivity

Reactivity

No reactivity hazard is expected.

Chemical Stability

Stable at normal temperatures and pressure.

Possibility of Hazardous Reactions

Will not polymerize.

Conditions to Avoid

Avoid heat, flames, sparks and other sources of ignition. Avoid contact with incompatible materials. Avoid contact with temperatures above 120 C.

Incompatible Materials

Strong acids. Strong oxidizer.

Hazardous decomposition products

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

Section 11: Toxicological Information

Information on Likely Routes of Exposure

Inhalation

May be harmful if inhaled.

Skin Contact

May cause skin irritation.

Eye Contact

Causes serious eye irritation.

Ingestion

Harmful if swallowed.

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Carbonic acid, calcium salt (1:1) (471-34-1)

Oral LD50 Rat 6450 mg/kg

Titanium dioxide (13463-67-7)

Oral LD50 Rat >10000 mg/kg

Organosilane (2768-02-7)

Oral LD50 Rat 7340 µL/kg

Dibutyltin oxide (818-08-6)

Oral LD50 Rat 44.9 mg/kg

Diisononyl phthalate (28553-12-0)

Oral LD50 Rat >9750 mg/kg

Inhalation LC50 Rat >4.4 mg/L 4 h (no deaths occurred)

Carbon black (1333-86-4)

Oral LD50 Rat >15400 mg/kg

Product Toxicity Data

Acute Toxicity Estimate

Oral	1261.241 mg/kg
------	----------------

Immediate Effects

Delayed Effects

May cause cancer. May damage fertility or the unborn child. Causes damage to organs. Causes damage to organs through prolonged or repeated exposure.

Irritation/Corrosivity Data

Causes serious eye irritation.

Respiratory Sensitization

No information on significant adverse effects.

Dermal Sensitization

No information on significant adverse effects.

Component Carcinogenicity

Titanium dioxide	13463-67-7
ACGIH:	A4 - Not Classifiable as a Human Carcinogen
IARC:	Monograph 93 [2010] ; Monograph 47 [1989] (Group 2B (possibly carcinogenic to humans))
DFG:	Category 3A (could be carcinogenic for man; inhalable fraction with the exception of ultra small particles)
OSHA:	Present
NIOSH:	Potential occupational carcinogen
Carbon black	1333-86-4
ACGIH:	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans
IARC:	Monograph 93 [2010] ; Monograph 65 [1996] (Group 2B (possibly carcinogenic to humans))
DFG:	Category 3B (could be carcinogenic for man; inhalable fraction)
OSHA:	Present
NIOSH:	Potential occupational carcinogen

Results of a DuPont epidemiology study showed that employees who had been exposed to titanium dioxide pigments were at no greater risk of developing lung cancer than were employees who had not been exposed to titanium dioxide pigments. No pulmonary fibrosis was found in any of the employees and no associations were observed between titanium dioxide pigment exposure and chronic respiratory disease or lung abnormalities. Based on the results of this study, DuPont concluded that titanium

dioxide pigment will not cause lung cancer or chronic respiratory disease in humans at concentrations experienced in the workplace.

Germ Cell Mutagenicity

No information on significant adverse effects.

Tumorigenic Data

No information on significant adverse effects.

Reproductive Toxicity

May damage fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure

Central nervous system.

Specific Target Organ Toxicity - Repeated Exposure

Respiratory system. Bladder.

Aspiration hazard

No information on significant adverse effects.

Medical Conditions Aggravated by Exposure

No data available.

Section 12: Ecological Information

Ecotoxicity

May cause long lasting harmful effects to aquatic life.

Component Analysis - Aquatic Toxicity

Diisononyl phthalate	28553-12-0
Fish:	LC50 96 h Brachydanio rerio >100 mg/L [semi-static]; LC50 96 h Lepomis macrochirus >0.14 mg/L [flow-through]; LC50 96 h Lepomis macrochirus >0.17 mg/L [static]; LC50 96 h Pimephales promelas >0.19 mg/L [flow-through]; LC50 96 h Pimephales promelas >0.14 mg/L [static]
Algae:	EC50 72 h Desmodesmus subspicatus >500 mg/L IUCLID ; EC50 96 h Pseudokirchneriella subcapitata >1.8 mg/L [static] EPA
Invertebrate:	EC50 48 h Daphnia magna >500 mg/L IUCLID ; EC50 48 h Daphnia magna >0.06 mg/L [Static] EPA

Section 13: Disposal Considerations

Disposal Methods

Dispose in accordance with all applicable federal, state/regional and local laws and regulations.

Component Waste Numbers

The U.S. EPA has not published waste numbers for this product's components.

Section 14: Transportation

US DOT Information:

Further information: Not regulated as dangerous goods

IATA Information:

Further information: Not regulated as dangerous goods

ICAO Information:

Further information: Not regulated as dangerous goods

IMDG Information:

Further information: Not regulated as dangerous goods

International Bulk Chemical Code

This material contains one or more of the following chemicals required by the IBC Code to be identified as dangerous chemicals in bulk.

Titanium dioxide	13463-67-7
IBC Code:	Category Z (slurry)

Section 15: Regulatory Information

U.S. Federal Regulations

None of this product's components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

SARA Section 311/312 (40 CFR 370 Subparts B and C) reporting categories

Carcinogenicity; Acute toxicity; Reproductive Toxicity; Serious Eye Damage/Eye Irritation; Specific Target Organ Toxicity

U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
Calcium carbonate	1317-65-3	No	Yes	Yes	Yes	Yes
Titanium dioxide	13463-67-7	No	Yes	Yes	Yes	Yes
Carbon black	1333-86-4	Yes	Yes	Yes	Yes	Yes

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65)



WARNING

This product can expose you to chemicals, including Titanium dioxide, Diisononyl phthalate, or Carbon black, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Titanium dioxide	13463-67-7
Carc:	carcinogen , 9/2/2011 (airborne, unbound particles of respirable size)
Diisononyl phthalate	28553-12-0
Carc:	carcinogen , 12/20/2013
Carbon black	1333-86-4
Carc:	carcinogen , 2/21/2003 (airborne, unbound particles of respirable size)

Canada Regulations

Canadian WHMIS Ingredient Disclosure List (IDL)

Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on MSDSs if they are included in products which meet WHMIS criteria specified in the Controlled Products Regulations and are present above the threshold limits listed on the IDL

Dibutyltin oxide	818-08-6
	1 %
Carbon black	1333-86-4
	1 %

Component Analysis - Inventory

Calcium carbonate (1317-65-3)

US	CA	E U	AU	PH	JP - ENC S	JP - ISH L	KR KEC I - Ann ex 1	KR KEC I - Ann ex 2	KR - REAC H CCA	C N	NZ	M X	T W	VN (Draf t)
Yes	NS L	EI N	Yes	Yes	Yes	Yes	Yes	No	No	Yes	Yes	Yes	Yes	Yes

Carbonic acid, calcium salt (1:1) (471-34-1)

US	CA	E U	AU	PH	JP - ENC S	JP - ISH L	KR KEC I - Ann ex 1	KR KEC I - Ann ex 2	KR - REAC H CCA	C N	NZ	M X	T W	VN (Draf t)
Yes	DS L	EI N	Yes	Yes	Yes	Yes	Yes	No	No	Yes	Yes	Yes	Yes	Yes

Titanium dioxide (13463-67-7)

US	CA	E U	AU	PH	JP - ENC S	JP - ISH L	KR KEC I - Ann ex 1	KR KEC I - Ann ex 2	KR - REAC H CCA	C N	NZ	M X	T W	VN (Draf t)
Yes	DS L	EI N	Yes	Yes	Yes	Yes	Yes	No	No	Yes	Yes	Yes	Yes	Yes

Organosilane (2768-02-7)

US	CA	E U	AU	PH	JP - ENC S	JP - ISH L	KR KEC I - Ann ex 1	KR KEC I - Ann ex 2	KR - REAC H CCA	C N	NZ	M X	T W	VN (Draf t)
Yes	DS L	EI N	Yes	Yes	Yes	Yes	Yes	No	No	Yes	Yes	No	Yes	Yes

Dibutyltin oxide (818-08-6)

US	CA	E U	AU	PH	JP - ENC S	JP - ISH L	KR KEC I - Ann ex 1	KR KEC I - Ann ex 2	KR - REAC H CCA	C N	NZ	M X	T W	VN (Draf t)
Yes	DS L	EI N	Yes	Yes	Yes	Yes	Yes	No	No	Yes	Yes	No	Yes	Yes

Diisononyl phthalate (28553-12-0)

US	CA	E U	AU	PH	JP - ENC S	JP - ISH L	KR KEC I - Ann ex 1	KR KEC I - Ann ex 2	KR - REAC H CCA	C N	NZ	M X	T W	VN (Draf t)
Yes	DS L	EI N	Yes	Yes	Yes	Yes	Yes	No	No	Yes	Yes	Yes	Yes	Yes

Carbon black (1333-86-4)

US	CA	E U	AU	PH	JP - ENC S	JP - ISH L	KR KEC I - Ann ex 1	KR KEC I - Ann ex 2	KR - REAC H CCA	C N	NZ	M X	T W	VN (Draf t)
Yes	DS L	EI N	Yes	Yes	Yes	Yes	Yes	No	No	Yes	Yes	Yes	Yes	Yes

Section 16: Other Information

Additional information on the product is available at. www.tccmaterials.com

Date of Preparation: May 11, 2021
 Version: 1.0

ProSpec® is a trademark of H.B. Fuller Construction Products Inc.

NOTE: The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to silica contained in our products. Before using any product, read its label and safety data sheet.