








	MEDIUM-DUTY REFRACTORY MORTAR	NON-SHRINK GROUT	WHITE GLASS BLOCK MORTAR	INSTANT POST CEMENT	INSTANT ANCHORING CEMENT	FAST-SETTING ANCHORING EPOXY	INSTANT WATER STOP
							
<b>USES &amp; ADVANTAGES</b>	<ul style="list-style-type: none"> <li>For fireplaces, fire pits, flues, etc.</li> <li>Good for applications up to 2550°F</li> <li>Air entrained for freeze-thaw resistance</li> <li>One hour working time</li> <li>ASTM C199</li> </ul>	<ul style="list-style-type: none"> <li>Capable of handling high load transfers</li> <li>MN DOT approved Non-Shrink Grouts</li> <li>ASTM C1107</li> <li>Corps of engineers spec. CRD-C 621</li> </ul>	<ul style="list-style-type: none"> <li>For use with glass block in shower or bathroom walls</li> <li>High-strength white mortar</li> <li>Minimizes joint shrinkage</li> <li>Mix with bonding additive for exterior applications</li> </ul>	<ul style="list-style-type: none"> <li>Sets fence posts, mailboxes, basketball poles, and swing sets</li> <li>No mixing required</li> <li>No bracing required</li> <li>Fast-setting</li> <li>Not for structural supports (footings)</li> </ul>	<ul style="list-style-type: none"> <li>Expands as it hardens</li> <li>Sets handrails, bolts, poles, and fixtures</li> <li>Use with concrete or masonry</li> <li>Sets in 20 minutes</li> </ul>	<ul style="list-style-type: none"> <li>High-strength</li> <li>Resists chemicals and solvents</li> <li>Moisture tolerant</li> <li>100% solids</li> <li>Fast-setting</li> <li>Non-sag</li> </ul>	<ul style="list-style-type: none"> <li>Bonds well to wet walls</li> <li>Sets in just 3-5 minutes</li> <li>Plugs holes in walls</li> <li>Seals water flow in basements</li> <li>Great for swimming pool repairs</li> </ul>
<b>COVERAGE</b>	<ul style="list-style-type: none"> <li>50 lb. bag yields .5 cu. ft. of wet mortar</li> <li>Will lay 80-100 standard fire bricks at 1/8" joint thickness</li> </ul>	<ul style="list-style-type: none"> <li>50 lb. bag yields 0.45 cu. ft., at a flowable consistency of wet mortar</li> </ul>	<ul style="list-style-type: none"> <li>50 lb. bag yields .5 cu. ft. of wet mortar</li> </ul>	<ul style="list-style-type: none"> <li>50 lb. bag will set a 3" post in a 6" diameter hole with a depth of 24"</li> </ul>	<ul style="list-style-type: none"> <li>10 lb. yields 170 cu. in. or anchors 2 fixtures in a 2" diameter hole with a depth of 2"</li> </ul>	<ul style="list-style-type: none"> <li>8.45 fl. oz. tube yields 30 lin. ft. at a 1/8" x 1/8" line</li> </ul>	<ul style="list-style-type: none"> <li>10 lb. yields 18 cu. in. or a crack 1" deep by 1/4" wide and 6' long</li> <li>25 lb. yields 45 cu. in. or a crack 1" deep by 1/4" wide and 15' long</li> </ul>
<b>APPLICATION</b>							
Interior & Exterior	X	X	X	X	X	X	X
Pre-Blended: Just Add Water	X	X	X	X	X	Ready to Use	X
Fast-Setting				X	X	X	X
Setting Fireplace Masonry Units	X						
Setting Glass Block			X				
Lead Transfer & Base Weight Distribution		X					
Setting Large Fixtures (6-12" diameter hole)				X			
Setting Small Fixtures (2-6" diameter hole)		X			X	X	
High Strength/Bond	X	X	X	X	X	X	X
Expands As It Sets					X		X
Low/Non-Shrink		X	X			X	