

## 1. PRODUCT NAME

Landscape Loc® Mulch & Rock Bond

## 2. MANUFACTURER

TCC Materials  
2025 Centre Pointe Blvd.  
Mendota Heights, MN 55120 USA  
Phone: 1.651.688.9116  
Web: [tccmaterials.com](http://tccmaterials.com)

## 3. PRODUCT DESCRIPTION

Landscape Loc Mulch & Rock Bond is a specially-formulated locking compound to stabilize mulch, rock, gravel, sand, and other ground cover. Landscape Loc prevents movement caused by rain, wind, wildlife, mowers, leaf blowers, pets, and other sources while allowing the substrate to drain and breathe. Sustain and enhance the natural look of your mulch. Landscape Loc has been tested and proven to be environmentally safe for ground and water. For best performance, use during the same growing season as purchased. Just shake well & use!

### Features and Benefits

- Easy to apply with sprayer (purchased separately)
- Reaches full bond in 24-48 hours
- Just shake well and use
- Goes on white and dries clear
- Allows surfaces to drain & breathe
- Environmentally safe
- Non toxic - safe for plants and animals
- Low VOC and EPA Compliant

### When/Where to Use

- Interior/exterior locations
- Landscape maintenance
- Edges/borders, trees, plant beds, slopes, leaf piles, erosion
- Mulch or wood chips
- Excellent around pools, ponds, driveways and walkways
- Sand and dirt
- Pebbles, light rock, and gravel
- Control of dust and erosion on gravel roads and commercial jobsites

## 4. TECHNICAL DATA

Landscape Loc Mulch & Rock Bond is manufactured with only the finest quality raw materials available and close quality-control is practiced.

### Available Size

- 1 gal. bottle (BOM #105146)
- 5 gal. pail (BOM #105337)

### Coverage

Coverage will vary from 250–750 sq. ft./gallon depending on weight, size, porosity and desired hold of material. Rock applications will require more product to get similar results, depending on the size, shape, and porosity of the rock and depth of application. Rock application will require more product to achieve similar results.

## 5. INSTALLATION

### Preparation

Read all directions before starting work. Place new mulch or arrange existing mulch to desired location and thickness. Apply when temperatures are above 50°F (10°C) and when there is no wind or rain expected within 24 hours. (Bond time will be longer with colder temperatures and shorter with higher temperatures.)

**Note:** It is the responsibility of the installer/applicator to ensure the suitability of the product for its intended use.

### Mixing

**SHAKE VIGOROUSLY OR STIR WELL TO ENSURE A UNIFORM MIX BEFORE APPLICATION.**

### Application

- Best when used during the same growing season as purchased.
- Use of a fan-tipped commercial sprayer for optimal results, but a garden sprayer may also be used.
- Apply when temperatures are above 50°F (10°C).
- Apply when no rain, wind, or frost is forecasted for 24 hours.
- Hold sprayer 1-2 feet away from surface.
- Spray lightly for light hold and thicker for heavier hold.
- Apply evenly or apply heavier where more hold is needed.
- Product will go on white and dry clear.
- Allow to dry for 24-48 hours for full bond.
- Apply a second coat, if desired for stronger hold.
- Reapply annually for best results.
- If settling occurs in container, shake well to remix.

### Clean Up

Use soapy water to clean hands and tools immediately after use. Excess product can be cleaned with water before product has dried.

### Limitations

- Follow all industry standard safety procedures when working with construction and landscape products.
- Always shake or stir to blend well just before use.
- Best when used during the same growing season as purchased.

### Safety

READ THE SAFETY DATA SHEET (SDS) BEFORE USING THIS PRODUCT. SDS information is available on our website: [tccmaterials.com](http://tccmaterials.com)

### Cautions

Read complete cautionary information printed on product container prior to use.

This Product Data Sheet has been prepared in good faith on the basis of information available at the time of publication. It is intended to provide users with information about and guidelines for the proper use and application of the covered brand product(s) under normal environmental and working conditions. Because each project is different, TCC Materials cannot be responsible for the consequences of variations in such conditions, or for unforeseen conditions.

## 6. AVAILABILITY

To locate products in your area, please contact:  
 Phone: 1.651.688.9116  
 Website: tccmaterials.com

## 7. WARRANTY

Seller warrants that its product will conform to and perform in accordance with the product specifications. The foregoing warranty is in lieu of all other warranties, expressed or implied, including, but not limited to those concerning merchantability and fitness for a particular purpose. Because of the difficulty in ascertaining and measuring damages hereunder, it is agreed that Seller's liability to the Buyer shall not exceed the total amount billed and billable to the Buyer for the product hereunder.



<b>Shelf Life</b>	Best when used within the same growing season as purchased in original, unopened container.
<b>Storage Conditions</b>	Store dry, 40-95°F (4-35°C), out of direct sunlight in tightly sealed original labeled container.
<b>Color</b>	Milky white liquid / dries to clear.

**SHAKE WELL BEFORE USING**

**KEEP PRODUCT IN CONTAINER FROM FREEZING**

**WARNING: INJURIOUS TO EYES**

**KEEP OUT OF REACH OF CHILDREN**

Landscape Loc® is a registered trademark of TCC Materials  
 2025 Centre Pointe Blvd.  
 Mendota Heights, MN 55120 USA  
 www.tccmaterials.com  
 ©Copyright 2021 TCC Materials



REV 05.21