






ADVANTAGES/USES	CURE & SEAL WB	CURE & SEAL WB 1315	CONCRETE & MASONRY SEALER WB	SALT BARRIER WB	CURE & HARDEN
					
	<ul style="list-style-type: none"> <li>• Low VOC, water based mix</li> <li>• Tack-free in 2-4 hours</li> <li>• Ready to use (no diluting)</li> <li>• Sprays white, dries clear</li> <li>• Interior or exterior application</li> <li>• new or existing applications</li> <li>• Concrete, masonry, terrazzo, brick, stone, masonry, and other cementitious materials</li> <li>• Seal many types of resilient floor coverings and prous tile</li> <li>• Commercial and residential applications</li> </ul>	<ul style="list-style-type: none"> <li>• Meets ASTM C1315 type 1 Class A</li> <li>• Low VOC, water-based mix</li> <li>• Tack-free in 2-4 hours</li> <li>• Ready to use</li> <li>• Sprays white, dries clear</li> <li>• Interior or exterior applications</li> <li>• Concrete, masonry, terrazzo, brick, stone, masonry, and other cementitious materials.</li> <li>• Decorative concrete</li> <li>• Commercial and residential applications</li> </ul>	<ul style="list-style-type: none"> <li>• Protects and seals</li> <li>• Repels water</li> <li>• Non-staining, colorless, non-yellowing</li> <li>• Ready to use</li> <li>• Breathable, does not trap moisture</li> <li>• Protects from effects of rain and other water penetration, chemicals, deicing salts, freeze-thaw, and smog</li> <li>• Exterior above-grade applications</li> <li>• Concrete, brick masonry, stucco, burnished or split-faced block, natural and synthetic stone, stucco, and other cementitious materials</li> </ul>	<ul style="list-style-type: none"> <li>• Non-gloss finish that won't change the surface appearance</li> <li>• Non-staining, non yellowing, dries tack-free</li> <li>• Ready to use</li> <li>• Waterbased formula provides breathable, deep penetrating protection that does not trap moisture</li> <li>• Repels water and protects from salt deterioration</li> <li>• Reduces efflorescence</li> <li>• Excellent for driveways and garages prone to salt damage from vehicle traffic</li> </ul>	<ul style="list-style-type: none"> <li>• Sodium silicate</li> <li>• Harden concrete surfaces</li> <li>• Improves abrasion resistance</li> <li>• Extends concrete service life</li> <li>• Aids in curing of newly finished concrete</li> <li>• Minimizes shrinkage cracking</li> <li>• Non-staining, non-yellowing</li> <li>• Ready to use</li> <li>• Water based, 0g/L VOC</li> <li>• Will not inhibit adhesion of secondary coatings or adhesives</li> </ul>
	APPLICATION				
	Finish Type	Satin	High Gloss	Natural Finish	Natural Finish
	VOC	<100 g/L	<150 g/L	211 g/L	0 g/L
	Dry Time	1-2 hours (touch) 4-12 hours (traffic) at 70°F	1-2 hours (touch) 4-12 hours (traffic) at 70°F	2-4 hours at 70°F(21°C)	2-4 hours at 70°F
	Coverage Rate	Curing: Broomed or Troweled - 200-300 Sq. Ft./Gal. Second Coat 300-500 Sq. Ft./Gal.	Curing: Broomed or Troweled - 200-300 Sq. Ft./Gal. Second Coat 300-500 Sq. Ft./Gal.	125 Sq. Ft. / gal, per coat	125-300 Sq. Ft. / gal, per coat
	Sizes Available	1 gal. bottle, 5 gal. pail, 55 gal. drum	1 gal. bottle, 5 gal. pail, 55 gal. drum	1 gal. bottle, 5 gal. pail, 55 gal. drum	1 gal. bottle, 5 gal. pail, 55 gal. drum

For Technical Product Data, Industry Standards, and Material Safety Data Sheets on all of the Tenon® products, please visit our website at [www.tenonsolutions.com](http://www.tenonsolutions.com)