

# SAFETY DATA SHEET Paver Guardian

# **SECTION 1) IDENTIFICATION**

Product ID: PaverGuardian

Product Name: Concrete Sealer

Revision Date: August 1, 2023 Date Printed: August 1, 2023

Version: 1.1 Supersedes Date: N. A.

Manufacturer's Name: TCC Materials Company

Address: 2025 CENTRE POINTE BLVD MENDOTA H EIGHTS, MN, US,55120

Emergency Phone: 800-424-9300 Information Phone Number:651-688-9116

Fax:

**Product/Recommended Uses:** 

# **SECTION 2) HAZARDS IDENTIFICATION**

# Classification

A spiration H azard- Category1

Carcinogenicity- Category1 B

Germ Cell Mutagenicity- Category1 B

# **Pictograms**



# Signal Word

D anger

## **Hazardous Statements - Health**

H304 - May be fatal if swallowed and enters airways

H350 - May cause cancer.

H340 - May cause genetic defects.

# **Precautionary Statements - General**

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P103 - Read label before use.

# **Precautionary Statements - Prevention**

P201 - O btain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

# **Precautionary Statements - Response**

P301 + P310 - IF SWALLOWED: I mmediately call a POI SON CENTE R or doctor.

Paver Guardian www.tccmaterials.com Page 1 of 7

P331 - Do NOT induce vomiting

P308 + P313 - IF exposed or concerned: Get medical advice/attention.

#### **Precautionary Statements - Storage**

P405 - Store locked up.

#### **Precautionary Statements - Disposal**

P501 - Dispose of contents/container in accordance with local/national/international regulations.

# **Hazards Not Otherwise Classified (HNOC)**

None.

#### Acute toxicity of 10% of the mixture is unknown

SECTION 3) COMPOSITION/INFORMATION ON INGREDIENTS				
CAS	Chemical Name	% By Weight		
0064742-95-6	AROMATIC HYDROCARBON MIXTURE >C9	76.92% - 100.00%		
P881257	POLYALKYLSILOXANE RESIN WITH ALKOXY AND HYDROXY GROUPS (PROVISIONAL)	7.60% - 11.40%		

# **SECTION 4) FIRST-AID MEASURES**

#### Inhalation

Remove source of exposure or move person to fresh air and keep comfortable for breathing.

If exposed/If you feel unwell/If concerned:

Get medical advice/attention.

#### **Eye Contact**

If irritation occurs, cautiously rinse eyes with lukewarm, gently flowing water for 5 minutes, while holding the eyelids open.

If eye irritation persists:

Get medical advice/attention.

#### **Skin Contact**

Rinse/wash with lukewarm, gently flowing water and mild soap for 5 minutes or until product is removed.

If skin irritation occurs or you feel unwell:

Get medical advice/attention .

IF exposed or concerned:

#### Ingestion

Immediately call a POISON CENTER or doctor.

Do NOT induce vomiting

If vomiting occurs naturally, lie on your side, in the recovery position.

Rinse mouth.

IF exposed or concerned:

Get medical advice/attention.

# Most Important Symptoms and Effects, Both acute and Delayed

No data available.

#### Indication of Any Immediate Medical Attention and Special Treatment Needed

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. No specific treatment is required.

#### **SECTION 5) FIRE-FIGHTING MEASURES**

#### **Suitable Extinguishing Media**

Small Fire: Dry chemical, foam, carbon dioxide, water-spray or alcohol-resistant foam. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Large Fire: Water spray, fog or alcohol-resistant foam.

## **Unsuitable Extinguishing Media**

Do not use straight stream of water.

#### Specific Hazards in Case of Fire

Fire will produce irritating gases.

#### **Fire-Fighting Procedures**

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Cool containers with flooding quantities of water until well after fire is out. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

#### **Special Protective Actions**

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

# **SECTION 6) ACCIDENTAL RELEASE MEASURES**

#### **Emergency Procedure**

Stay uphill and/or upstream. Ventilate closed spaces before entering. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing. Evacuate and isolate hazard area and keep unauthorized personnel away.

#### **Recommended Equipment**

Wear chemical protective clothing and positive pressure self-contained breathing apparatus (SCBA).

#### **Personal Precautions**

Do not breathe vapor or mist. Do not get on skin, eyes or clothing.

#### **Environmental Precautions**

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

#### Methods and Materials for Containment and Cleaning Up

Absorb Liquids in vermiculite, dry sand, earth, or similar inert material and deposit in sealed containers for disposal. Ventilate area after clean-up is complete.

# **SECTION 7) HANDLING AND STORAGE**

#### General

Wash hands after use. Avoid contact with skin, eye or clothing. Avoid breathing vapor or mist. Use good personal hygiene practices. Eating, drinking and smoking in work areas is prohibited. Remove contaminated clothing and protective equipment before entering eating areas. Eyewash stations and showers should be available in areas where this material is used and stored All containers must be properly labelled.

#### **Ventilation Requirements**

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source. Report ventilation failures immediately.

## **Storage Room Requirements**

Store in a cool, dry, well ventilated area, away from sources of ignition and incompatibilities. Keep containers securely sealed when not in use. Containers that have been opened must be carefully resealed to prevent leakage. Indoor storage should meet OSHA standards and appropriate fire codes. Empty containers retain residue and may be dangerous.

# **SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION**

# **Eye Protection**

Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working with liquids.

# **Skin Protection**

Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Use of chemical resistant gloves classified under Standard EN374: Protective gloves against chemicals and microorganisms. Examples of preferred glove barrier materials include: Butyl rubber, Polyethylene, Chlorinated polyethylene, Ethyl vinyl alcohol laminate ("EVAL"). Examples of acceptable glove barrier materials include: Viton, Neoprene, Polyvinyl chloride ("PVC" or "vinyl"), Nitrile/butadiene rubber ("nitrile" or "NBR").

 $Full\ contact\ Material:\ butyl-rubber\ Minimum\ layer\ thickness:\ 0.3\ mm\ Break\ through\ time:\ 480\ min$ 

Material tested: Butoject® (KCL 897 / Aldrich 2677647, Size M).

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.4 mm Break through time: 30 min

Material tested: Camatril® (KCL 730 / Aldrich 2677442, Size M).

Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to **EN** 374) is recommended. When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber. Launder soiled clothes or properly disposed of contaminated material, which cannot be decontaminated.

# **Respiratory Protection**

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 should be followed. Check with respiratory protective equipment suppliers.

# **Appropriate Engineering Controls**

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value

Chemical	ACGIH TWA	ACGIH TWA (ppm)	ACGIH STEL	ACGIH STEL	ACGIH	ACGIH	ACGIH	OSHA TWA
Name	(mg/m3)		(mg/m3)	(ppm)	Carcinogen	TLV Basis	Notations	(mg/m3)
AROMATIC HYDROCARBO N MIXTURE >C9	[(L][N159](L] [N800)); [5 (I) [N159]5 (I] [N800));	(L}[N159](L} [N800)			[A2[N159]A2 [N800)); [A4 [N159]A4 [N800));	URT irr [N159]URT irr [N800)	[A2[N159]A2 [N800)); [A4 [N159]A4 [N800));	2000

Chemical Name	OSHA TWA (ppm)	OSHA STEL (mg/m3)	OSHA STEL (ppm)	OSHA Carcinogen	OSHA Skin designation	OSHA Tables (21, 22, 23)	NIOSH TWA (mg/m3)	NIOSH TWA (ppm)
AROMATIC HYDROCARBO N MIXTURE >C9	500							

Chemical	NIOSH STEL (mg/m3)	NIOSH STEL	NIOSH
Name		(ppm)	Carcinogen
AROMATIC HYDROCARBO N MIXTURE >C9			

URT - Upper respiratory tract

# **SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES**

#### **Physical and Chemical Properties**

Density	7.39637 lb/gal
Specific Gravity	0.88628
% Solids By Weight	8.07500%
Appearance	N/A
Odor Description	N/A
pH	N/A
Water Solubility	N/A
Flammability	N/A

Flash Point	N/A
Viscosity	N/A
Lower Explosion Level	N/A
Upper Explosion Level	N/A
Vapor Density	N/A
Freezing Point	N/A
Melting Point	N/A
Low Boiling Point	N/A
Evaporation Rate	N/A
Coefficient Water/Oil	N/A

# **SECTION 10) STABILITY AND REACTIVITY**

#### **Stability**

Stable under normal storage and handling conditions.

#### **Conditions To Avoid**

Avoid heat, sparks, flame and contact with incompatible materials

# **Hazardous Reactions/Polymerization**

Will not occur.

## **Incompatible Materials**

Strong bases, acids, and oxidizing agents.

# **Hazardous Decomposition Products**

Oxides of carbon.

# **SECTION 11) TOXICOLOGICAL INFORMATION**

# **Acute Toxicity**

Based on available data, the classification criteria are not met.

The Acute Toxicity Estimate (ATE) for an oral exposure to this mixture is >5000 mg/kg body weight

The Acute Toxicity Estimate (ATE) for a dermal exposure to this mixture is >5000 mg/kg body weight

The Acute Toxicity Estimate (ATE) for an inhalation (vapour) exposure to this mixture is >20 mg/l

# **Aspiration Hazard**

May be fatal if swallowed and enters airways

# Carcinogenicity

May cause cancer.

# **Germ Cell Mutagenicity**

May cause genetic defects.

# **Reproductive Toxicity**

Based on available data, the classification criteria are not met.

# **Respiratory/Skin Sensitization**

Based on available data, the classification criteria are not met.

# Serious Eye Damage/Irritation

Based on available data, the classification criteria are not met.

# Skin Corrosion/Irritation

Based on available data, the classification criteria are not met.

## **Specific Target Organ Toxicity - Repeated Exposure**

Based on available data, the classification criteria are not met.

# **Specific Target Organ Toxicity - Single Exposure**

Based on available data, the classification criteria are not met.

#### **Likely Routes of Exposure**

Inhalation, Ingestion, Skin contact, Eye contact

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

#### **Potential Health Effects - Miscellaneous**

#### 0064742-95-6 AROMATIC HYDROCARBON MIXTURE >C9

The following medical conditions may be aggravated by exposure: skin disorders. Laboratory studies with rats have shown that petroleum distillates can cause kidney damage and kidney or liver tumors. These effects were not seen in similar studies with guinea pigs, dogs, or monkeys. Several studies evaluating petroleum workers have not shown a significant increase of kidney damage or an increase in kidney or liver tumors.

# **SECTION 12) ECOLOGICAL INFORMATION**

# **Toxicity**

Based on available data, the classification criteria are not met.

#### **Mobility in Soil**

No data available.

#### **Bioaccumulative Potential**

No data available.

## **Persistence and Degradability**

No data available.

#### **Other Adverse Effects**

No data available.

# **SECTION 13) DISPOSAL CONSIDERATIONS**

### **Waste Disposal**

It is the responsibility of the user of the product to determine at the time of disposal whether the product meets local criteria for hazardous waste. Waste management should be in full compliance with national, state and local laws. Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes.

# **SECTION 14) Transport Information**

	U.S. DOT Information	IMDG Information	IATA Information
UN number:	Not Regulated	Not Regulated	Not Regulated
Proper shipping name:	N/A	N/A	N/A
Hazard class:	Not Applicable	Not Applicable	Not Applicable
Packaging group:	Not Applicable	Not Applicable	Not Applicable
Hazardous substance (RQ):	No Data Available		
Marine Pollutant:	No Data Available	No Data Available	
Note / Special Provision:	No Data Available	No Data Available	No Data Available
Toxic-Inhalation Hazard:	No Data Available		

#### **SECTION 15) REGULATORY INFORMATION**

#### Safety, health and environmental regulations

The product has been evaluated against the following relevant regulations: U.S.A Toxic Substance Control Act (TSCA) California Proposition 65 Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312 Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313 Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) Section 103

CAS	Chemical Name	% By Weight	Regulation List
0064742-95-6	AROMATIC HYDROCARBON MIXTURE >C9	76.92% - 100.00%	SARA312,TSCA
P881257	POLYALKYLSILOXANE RESIN WITH ALKOXY AND HYDROXY GROUPS (PROVISIONAL)	7.60% - 11.40%	SARA312,TSCA

# **SECTION 16) OTHER INFORMATION**

#### Glossary

ACGIH - American Conference of Governmental Industrial Hygienists; CAS - Chemical Abstracts Service; Chemtrec - Chemical Transportation Emergency Center; DSL - Domestic Substances List; ESL- Effects screening levels; GHS - "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations; HMIS - Hazardous Material Information Service; IATA - Dangerous Goods Regulations (DGR) for the air transport (IATA); IMDG - International Maritime Dangerous Goods Code; LC - Lethal Concentration; LD - Lethal Dose; NFPA - National Fire Protection Association; OEL - Occupational Exposure Limit; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL - Permissible Exposure Limit; SARA 313 - Superfund Amendments and Reauthorization Act, Section 313; SCBA - Self Contained Breathing Apparatus; ppm - parts per million; STEL - Short-term exposure limit; TLV - Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time-weighted average; US DOT- US Department of Transportation.

#### Version 1.0:

Revision Date: Aug 01, 2023

First Edition.

#### **DISCLAIMER**

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

Paver Guardian www.tccmaterials.com Page 7 of 7