










# HARDSCAPE/LANDSCAPE SELECTION GUIDE

	LANDSCAPE LOC MULCH & ROCK BOND	TECHMIX PREMIUM COUNTERTOP MIX	TENON REFRACTORY MORTAR	TENON SELF-LEVELING RESURFACER	TENON PARTIAL DEPTH CONCRETE PATCH
					<b>IMAGE COMING SOON</b>
<b>FEATURES</b>	<ul style="list-style-type: none"> <li>• Easy to apply with sprayer</li> <li>• Ready to use/no dilution</li> <li>• Reaches full bond in 24-48 hours</li> <li>• Goes on white and dries clear</li> <li>• Allows surface to drain and breathe</li> <li>• Environmentally safe</li> <li>• Non-toxic - safe for plants and animals</li> <li>• Low VOC and EPA compliant</li> </ul>	<ul style="list-style-type: none"> <li>• Polymer modified</li> <li>• Air entrained, freeze-thaw durable for exterior use</li> <li>• High-strength</li> <li>• 4,000 psi at 24 hours</li> <li>• 10,000 psi at 28 days</li> <li>• Self-leveling consistency</li> <li>• Can be demolded in 18-24 hours</li> <li>• Just add water</li> </ul>	<ul style="list-style-type: none"> <li>• Good for applications up to 2250°F</li> <li>• Indoor/outdoor applications</li> <li>• Air-entrained for freeze-thaw resistance</li> <li>• One hour working time</li> <li>• Great workability and high-strength</li> <li>• Meets or exceeds ASTM C199</li> <li>• Hydraulic mortar, once cured becomes water insoluble and acid resistant</li> </ul>	<ul style="list-style-type: none"> <li>• Sets in approximately 75-90 minutes</li> <li>• Provides a smooth, hard, flat surface</li> <li>• Underlayment or wear surface</li> <li>• Accepts foot traffic in 6 hours</li> <li>• Applications from &lt; 1/8 inch to 1 inch</li> </ul>	<ul style="list-style-type: none"> <li>• Preblended mixtures (2:1, 2:5:1 and 3:1 blends)</li> <li>• High compressive strength</li> <li>• Durable patching material</li> <li>• No pea gravel</li> <li>• Meets ASTM C387 for high-early and normal strength</li> </ul>
<b>USES &amp; ADVANTAGES</b>	<ul style="list-style-type: none"> <li>• Interior/exterior locations</li> <li>• Edges/borders, trees, plant beds, walks, driveways, slopes, leaf piles, erosion</li> <li>• Control of dust and erosion on gravel roads and commercial job sites</li> </ul>	<ul style="list-style-type: none"> <li>• Precast countertops</li> <li>• Outdoor kitchen tops</li> <li>• Precast wall caps</li> <li>• Precast mantels</li> <li>• Precast lintels</li> </ul>	<ul style="list-style-type: none"> <li>• Outdoor fireplaces and fire pits</li> <li>• Setting clay flue liners</li> <li>• Set or parging of smoke chambers</li> </ul>	<ul style="list-style-type: none"> <li>• New concrete floor slabs with unacceptable finishes</li> <li>• Damaged existing concrete</li> <li>• Interior and exterior concrete applications</li> </ul>	<ul style="list-style-type: none"> <li>• Paver bonding mortar</li> <li>• Slab stone setting mortar</li> <li>• Partial depth repair of concrete pavements</li> <li>• Shallow depth repairs between 1/2-2 inches</li> </ul>
<b>FOR BEST PERFORMANCE</b>	<ul style="list-style-type: none"> <li>• Apply when temperatures are above 50°F</li> <li>• Apply when no rain, wind, or frost is forecasted for 24 hours</li> </ul>	<ul style="list-style-type: none"> <li>• Apply when temperatures are above 50°F</li> <li>• Minimum thickness 1.5 inches</li> <li>• Maximum thickness 8 inches</li> <li>• Do not exceed water limits</li> </ul>	<ul style="list-style-type: none"> <li>• Do not apply in direct sunlight</li> <li>• Do not apply on hot or windy days</li> <li>• Do not apply when rain is forecasted within 24 hours</li> <li>• Mix only the amount that can be placed in 60 minutes</li> </ul>	<ul style="list-style-type: none"> <li>• Do not over-trowel or overdo work</li> <li>• Apply when temperatures are above 50°F-90°F</li> <li>• Apply only to surfaces that are frost free</li> </ul>	<ul style="list-style-type: none"> <li>• Use a mechanical batch mixer</li> <li>• Pre-wet surface just prior to application</li> <li>• Do not overwork the concrete mixture</li> </ul>
<b>SIZE</b>	<ul style="list-style-type: none"> <li>• 1 gal bottle</li> <li>• 5 gal pail</li> </ul>	<ul style="list-style-type: none"> <li>• 50 lb bag - gray</li> <li>• 50 lb bag - white</li> </ul>	<ul style="list-style-type: none"> <li>• 10 lb pail</li> <li>• 50 lb bag</li> </ul>	<ul style="list-style-type: none"> <li>• 50 lb bag - gray</li> </ul>	<ul style="list-style-type: none"> <li>• 50 lb bag</li> </ul>

# HARDSCAPE/LANDSCAPE SELECTION GUIDE

	TENON INSTANT HYDRAULIC CEMENT	TENON INSTANT ANCHORING CEMENT	TENON CONCRETE & MASONRY DISSOLVER	TENON RESTORATION CLEANER	TENON SALT BARRIER
					
<b>FEATURES</b>	<ul style="list-style-type: none"> <li>Bonds to wet walls</li> <li>Sets in 3-5 minutes</li> <li>Just add water, mix and use</li> <li>Stops seepage leaks</li> <li>Interior and exterior use</li> <li>Above and below grade</li> <li>Paintable when cured</li> </ul>	<ul style="list-style-type: none"> <li>Expands as it hardens to set securely</li> <li>Accelerated, sets in approximately 20 minutes</li> <li>Excellent flowability and workability</li> <li>Add water, mix and use</li> </ul>	<ul style="list-style-type: none"> <li>Ready to use (no mixing or diluting)</li> <li>Begins to work immediately upon application</li> <li>100% biodegradable</li> <li>Non-toxic to plants and vegetation</li> <li>Does not contain any harmful acids</li> <li>Non-corrosive and non-fuming</li> </ul>	<ul style="list-style-type: none"> <li>Cleans and restores</li> <li>Dissolves mineral deposits</li> <li>Surface preparation product</li> <li>Ready to use</li> </ul>	<ul style="list-style-type: none"> <li>Natural looking invisible protection</li> <li>Ready to use (no diluting)</li> <li>Dries tack free</li> <li>High alkali resistance</li> <li>Easy to apply with sprayer and roller</li> <li>Protects from effects of rain and other water penetration, salt, freeze-thaw and smog</li> </ul>
<b>USES &amp; ADVANTAGES</b>	<ul style="list-style-type: none"> <li>Plugs holes in walls</li> <li>Seals water flow in ponds or fountains</li> <li>Swimming pool repairs</li> </ul>	<ul style="list-style-type: none"> <li>Interior/exterior</li> <li>Sets handrails, bolts, poles and fixtures</li> </ul>	<ul style="list-style-type: none"> <li>Removes unwanted Portland cement-based residue</li> <li>Safely removes mortar from painted surfaces</li> </ul>	<ul style="list-style-type: none"> <li>Brick</li> <li>Masonry</li> <li>Concrete</li> <li>Precast concrete elements</li> <li>Retaining walls</li> </ul>	<ul style="list-style-type: none"> <li>Above grade exterior applications</li> <li>Vertical or horizontal applications</li> <li>Concrete, masonry, pavers, brick, retaining walls, stucco, block, stone, and other cementitious materials</li> </ul>
<b>FOR BEST PERFORMANCE</b>	<ul style="list-style-type: none"> <li>Apply only to surfaces that are frost free and above 40°F</li> <li>Do not apply on painted surfaces</li> <li>Mix with clean water only</li> </ul>	<ul style="list-style-type: none"> <li>Do not apply in temperatures below 40°F</li> <li>Let set for one hour minimum before applying torque to bolt or fixture</li> </ul>	<ul style="list-style-type: none"> <li>Apply only to dry surfaces</li> <li>Do not allow to dry on surfaces</li> <li>Allow to penetrate 10-15 minutes</li> <li>Rinse once concentrate has begun to soften</li> </ul>	<ul style="list-style-type: none"> <li>Always wet surface just prior to application</li> <li>Let the cleaner stand for 3-5 minutes</li> <li>Do not allow product to dry on surface</li> </ul>	<ul style="list-style-type: none"> <li>Do not apply when rain is expected within 4-6 hours</li> <li>Cleaned or washed surfaces must dry 3-7 days prior to application</li> </ul>
<b>SIZE</b>	<ul style="list-style-type: none"> <li>10 lb pail</li> <li>50 lb pail</li> </ul>	<ul style="list-style-type: none"> <li>10 lb pail</li> <li>50 lb pail</li> </ul>	<ul style="list-style-type: none"> <li>28 oz sprayer</li> <li>1 gal bottle</li> <li>5 gal pail</li> </ul>	<ul style="list-style-type: none"> <li>1 gal bottle</li> <li>5 gal pail</li> </ul>	<ul style="list-style-type: none"> <li>1 gal bottle</li> <li>5 gal pail</li> <li>55 gal drum</li> </ul>