# Benefits from sealing:

- Longer patio life
- Protection from grease, oil, coffee, salt/road spray, and pool chemicals, & more
- Withstands freeze/thaw
- Resists color fading



# CHECK OUT OUR NORTHROCK® LANDSCAPE LOC® MULCH & ROCK BOND



SEALED/PROTECTED UNSEALED



A TCC MATERIALS COMPANY

Phone 651-688-9116 info@tccmaterials.com

WWW.TCCMATERIALS.COM REV. 09/21





WWW.TCCMATERIALS.COM

### WATERBORNE SEALERS

#### PAVER GUARDIAN WB



- Waterborne sealer that protects against damaging freeze-thaw cycles, de-icing salts, & efflorescence while enhancing the surface appearance Invisible protection - will not alter
- color • Covers approximately 40-200 sq. ft. per gallon

DRYING TIME	2-4 hours	ALL THE
ACTIVE	8 %	
FINISH	Invisible	

#### PAVER SEAL PRO WB



- Waterborne sealer that protects against damaging freeze-thaw cycles, de-icing salts, & efflorescence while enhancing the surface appearance · Resists wear patterns from foot and vehicular traffic
  - Covers approximately 200-50 sq. ft. per gallon

DRYING TIME	1 hr (touch) / 2 hr (traffic)	
SOLIDS	10%	
FINISH	Natural	

### **PAVER SEAL & SHINE PRO WB**



- Waterborne sealer that protects against damaging freeze-thaw cycles, de-icing salts, & efflorescence while enhancing the surface appearance Resists wear patterns from foot and vehicular traffic
- Covers approximately 200-500 sq. ft. per gallon

DRYING TIME	1 hr (touch) / 2 hr (traffic)	
SOLIDS	19%	
FINISH	Gloss	

## **SOLVENT-BASED SEALERS**

#### PAVER GUARDIAN



1

DRYING TIME

ACTIVE FINISH

) elela

TENON

- · Solvent-based penetrating sealer that protects cementitious substrates from the deteriorating effects of salts and common chlorides used to aid snow and ice melting
- Covers approximately 40-200 sg. ft. per gallon

	and the second
hr (touch) / 2 hr (traffic)	C. S. M.
10%	Sec. 1
Invisible	

#### PAVER SEAL

- Solvent-based coating that forms a membrane to increase protection from damaging freeze-thaw cycles, de-icing salts, and chemical erosion
- Minimizes spalling and aggregate pop out
- Covers approximately 200-300 sq. ft. per gallon

	DRYING TIME	1-2 hrs (touch) 4-12 hrs (traffic)	3
	SOLIDS	25%	
[	FINISH	Matte	No.

### **PAVER SEAL & SHINE**



DRYING TIME

SOLIDS

FINISH

- Solvent-based coating that forms a membrane to increase protections from damaging freeze-thaw cycles, de-icing salts, and chemical erosion
  - Minimizes spalling and aggregate pop out
- Covers approximately 300-500 sq. ft. per gallon

1 hr (touch) / 2 hr (traffic)	
25%	
Gloss	

#### PAVER SEAL ULTRA SHINE



- Solvent-based coating that forms a membrane to increase protection from damaging freeze-thaw cycles, de-icing salts, and chemical erosion
- Minimizes spalling and aggregate pop out
- Covers approximately 300-500 sq. ft. per gallon

DRYING TIME	1 hr (touch) / 2 hr (traffic)
SOLIDS	30%
FINISH	High Gloss

# **CLEANERS**

# **PAVER WASH**



- · Removes efflorescence, light rust, and organic stains
- Cleans and restores paver surface and color
- Prepares pavers and stone surfaces prior to sealing
- Does not contain muriatic or hydrochloric acids
- Cleans approximately 150-250 sg. ft. per gallon

# DON'T FORGET TO CLEAN **BEFORE YOU SEAL!**

