



### SECTION 1) IDENTIFICATION

**Product ID:** Feather Patch Pro  
**Product Name:** Cementitious repair mortar  
**Revision Date:** July 27, 2023 **Date Printed:** July 27, 2023  
**Version:** 1.1 **Supersedes Date:** N.A.  
**Manufacturer's Name:** TCC Materials Company  
**Address:** 2025 CENTRE POINTE BLVD, MENDOTA HEIGHTS, MN, US, 55120  
**Emergency Phone:** 800-424-9300  
**Information Phone Number:** 651-688-9116  
**Fax:**  
**Product/Recommended Uses:**

### SECTION 2) HAZARDS IDENTIFICATION

#### Classification

Acute toxicity Dermal - Category 4  
Acute toxicity Oral - Category 5  
Carcinogenicity - Category 1A  
Reproductive Toxicity - Category 1A  
Respiratory Sensitizer (Solid/Liquid) - Category 1  
Serious Eye Damage - Category 1  
Skin Corrosion - Category 1B  
Skin Sensitizer - Category 1  
Specific Target Organ Toxicity - Repeated Exposure - Category 1  
Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) - Category 3

#### Pictograms



#### Signal Word

Danger

#### Hazardous Statements - Health

H312 - Harmful in contact with skin  
H303 - May be harmful if swallowed  
H350 - May cause cancer  
H360 - May damage fertility or the unborn child  
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled  
H314 - Causes severe skin burns and eye damage

H317 - May cause an allergic skin reaction

H372 - Causes damage to organs through prolonged or repeated exposure.

H335 - May cause respiratory irritation

#### **Precautionary Statements - General**

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P103 - Read label before use.

#### **Precautionary Statements - Prevention**

P280 - Wear protective gloves,protective clothing,eye protection/face protection.

P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P284 - Wear respiratory protection.

P260 - Do not breathe dust/fume/gas/mist/vapors/spray.

P264 - Wash thoroughly after handling.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P270 - Do not eat, drink or smoke when using this product.

P271 - Use only outdoors or in a well-ventilated area.

P233 - Keep container tightly closed.

#### **Precautionary Statements - Response**

P302 + P352 - IF ON SKIN: Wash with plenty of water.

P312 - Call a POISON CENTER/doctor if you feel unwell.

P321 - Specific treatment (see First-Aid on this label).

P362 + P364 - Take off contaminated clothing. And wash it before reuse.

P308 + P313 - IF exposed or concerned: Get medical advice/attention.

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P342 + P311 - If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 - Immediately call a POISON CENTER or doctor.

P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P363 - Wash contaminated clothing before reuse.

P333 + P313 - If skin irritation or a rash occurs: Get medical advice/attention.

#### **Precautionary Statements - Storage**

P405 - Store locked up.

P403 + P405 - Store in a well-ventilated place. Store locked up.

#### **Precautionary Statements - Disposal**

P501 - Dispose of contents/container in accordance with local/national/international regulations.

#### **Hazards Not Otherwise Classified (HNOC)**

None.

## **SECTION 3) COMPOSITION/INFORMATION ON INGREDIENTS**

CAS	Chemical Name	GHS Classifications	% By Weight
0065997-15-1	PORTLAND CEMENT SILICATE	Acute Tox. Derm. 4, H312; Eye Dam. 1, H318; Resp. Sens. 1, H334; Skin Corr. 1B, H314; Skin Sens. 1, H317; STOT SE 3 (Resp.), H335	30.00% - 50.00%
0065997-16-2	CEMENT, ALUMINA, CHEMICALS	Acute Tox. Derm. 4, H312; Acute Tox. Oral 4, H302; Aquatic Chronic 4, H413; Carc. 1A, H350; Eye Dam. 1, H318; Resp. Sens. 1, H334; Skin Corr. 1B, H314; Skin Sens. 1, H317	20.00% - 50.00%
0001317-65-3	CALCIUM CARBONATE	Carc. 1A, H350; STOT RE 2, H373	0.00% - 5.00%
0000554-13-2	LITHIUM CARBONATE	Acute Tox. Inh. 4, H332; Acute Tox. Oral 4, H302; Aquatic Acute 2, H401; Eye Irr. 2B, H320; Repr. 1A, H360	0.00% - 1.00%

## SECTION 4) FIRST-AID MEASURES

### Inhalation

Remove source of exposure or move person to fresh air and keep comfortable for breathing.

If breathing is difficult, trained personnel should administer emergency oxygen if advised to do so by the POISON CENTER/doctor.

Immediately call a POISON CENTER or doctor.

Take precautions to ensure your own safety (e.g. wear appropriate protective equipment).

### Eye Contact

Gently brush product off face.

Do not rub eyes.

Let the eyes water naturally for a few minutes.

Look right and left, then up and down.

Do not attempt to manually remove anything from the eyes.

Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open.

Remove contact lenses, if present and easy to do.

Continue rinsing for a duration of 30 minutes or until medical aid is available.

Take care not to rinse contaminated water into the unaffected eye or onto the face.

Immediately call a POISON CENTER or doctor.

Avoid direct contact. Wear chemical protective gloves, if necessary.

### Skin Contact

Wash contaminated clothing before re-use or discard.

Take off immediately all contaminated clothing, shoes and leather goods (e.g. watchbands, belts).

Rinse skin with lukewarm, gently flowing water/shower for a duration of 30 minutes or until medical aid is available.

Immediately call a POISON CENTER or doctor.

### Ingestion

Rinse mouth.

Do NOT induce vomiting.

Immediately call a POISON CENTER or doctor. If vomiting occurs naturally, lie on your side, in the recovery position.

### Most important symptoms and effects, both acute and delayed

No data available.

### Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. No specific treatment is required. No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Treat according to symptoms (decontamination, vital functions), no known specific antidote. Treatment should be supportive and based on the judgement of the physician in response to the reaction of the patient.

## SECTION 5) FIRE-FIGHTING MEASURES

### Suitable Extinguishing Media

Small Fire : Dry chemical, foam, carbon dioxide, water-spray or alcohol-resistant foam. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Large Fire : Water spray, fog or alcohol-resistant foam.

### Unsuitable Extinguishing Media

Do not use straight stream of water.

### Specific Hazards in Case of Fire

Fire will produce irritating and corrosive gases.

### Fire-fighting Procedures

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Cool containers with flooding quantities of water until well after fire is out. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

### Special Protective Actions

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

## SECTION 6) ACCIDENTAL RELEASE MEASURES

### Emergency Procedure

Ventilate closed spaces before entering. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing. Evacuate and isolate hazard area and keep unauthorized personnel away.

### Recommended Equipment

Wear chemical protective clothing and positive pressure self-contained breathing apparatus (SCBA). Breathing protection is required.

### Personal Precautions

Do not breathe dust. Do not get on skin, eyes or clothing.

### Environmental Precautions

Stop spill/release if it can be done safely. Prevent spilled material and water from clean-up/firefighting from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

### Methods and Materials for Containment and Cleaning up

Avoid raising dust. Safely collect powdered material and deposit in sealed containers for disposal. Ventilate and wash area after clean-up is complete

## SECTION 7) HANDLING AND STORAGE

### General

Wash hands after use. Use good personal hygiene practices. Eating, drinking and smoking in work areas is prohibited. Remove contaminated clothing and protective equipment before entering eating areas. Eyewash stations and showers should be available in areas where this material is used and stored All containers must be properly labelled. Do not get in eyes, on skin, or on clothing. Do not breathe dust.

### Ventilation Requirements

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source. Report ventilation failures immediately.

### Storage Room Requirements

Store in a cool, dry, well ventilated area, away from sources of ignition and incompatibilities. Keep containers securely sealed when not in use. Containers that have been opened must be carefully resealed to prevent leakage. Indoor storage should meet OSHA standards and appropriate fire codes. Empty containers retain residue and may be dangerous.

## SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

### Eye protection

Wear Dust-proof goggles with side shields

## Skin Protection

Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Use of chemical resistant gloves classified under Standard EN374: Protective gloves against chemicals and microorganisms. Examples of preferred glove barrier materials include: Butyl rubber, Polyethylene, Chlorinated polyethylene, Ethyl vinyl alcohol laminate ("EVAL"). Examples of acceptable glove barrier materials include: Viton, Neoprene, Polyvinyl chloride ("PVC" or "vinyl"), Nitrile/butadiene rubber ("nitrile" or "NBR").

Full contact Material: butyl-rubber Minimum layer thickness: 0.3 mm Break through time: 480 min

Material tested: Butoject® (KCL 897 / Aldrich Z677647, Size M).

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.4 mm Break through time: 30 min

Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M).

Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended.

It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers.

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves.

Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity.

Always seek advice from glove suppliers.

Contaminated gloves should be replaced.

Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber.

Launder soiled clothes or properly disposed of contaminated material, which cannot be decontaminated.

## Respiratory protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 should be followed.

Check with respiratory protective equipment suppliers.

## Appropriate Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

Chemical Name	ACGIH TWA (mg/m3)	ACGIH TWA (ppm)	ACGIH STEL (mg/m3)	ACGIH STEL (ppm)	ACGIH Carcinogen	ACGIH TLV Basis	ACGIH Notations	OSHA TWA (mg/m3)
CALCIUM CARBONATE								[15]; [5 (a)];
CEMENT, ALUMINA, CHEMICALS	1 (R)				A4	Pneumoconiosis; LRT irr; neurotoxicity	A4	
PORTLAND CEMENT SILICATE	1 (E,R)				A4	Pulm func; resp symptoms; asthma	A4	[15]; [5 (a)]; [50 mppcf];

Chemical Name	OSHA TWA (ppm)	OSHA STEL (mg/m3)	OSHA STEL (ppm)	OSHA Carcinogen	OSHA Skin designation	OSHA Tables (Z1, Z2, Z3)	NIOSH TWA (mg/m3)	NIOSH TWA (ppm)
CALCIUM CARBONATE						1	10,5a	
CEMENT, ALUMINA, CHEMICALS								
PORTLAND CEMENT SILICATE						[1]; [3];	10,5a	

Chemical Name	NIOSH STEL (mg/m3)	NIOSH STEL (ppm)	NIOSH Carcinogen
CALCIUM CARBONATE			
CEMENT, ALUMINA, CHEMICALS			
PORTLAND CEMENT			

(C) - Ceiling limit, (I) - Inhalable fraction, (R) - Respirable fraction, A2 - Suspected Human Carcinogen, A4 - Not Classifiable as a Human Carcinogen, func - Function, irr - Irritation, LRT - Lower respiratory tract, pulm - Pulmonary, resp - respiratory, URT - Upper respiratory tract

The information in this Section does not list non-hazardous components that might have relevant NIOSH Carcinogen, OSHA TWA (ppm), OSHA Tables (Z1, Z2, Z3), NIOSH TWA (mg/m<sup>3</sup>), ACGIH TWA (mg/m<sup>3</sup>), ACGIH Carcinogen, ACGIH TLV Basis, ACGIH Notations, OSHA TWA (mg/m<sup>3</sup>) regulatory values, if they are present at less than 1%. Please contact manufacturer for more information.

## SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

### Physical and Chemical Properties

Density	20.07250 lb/gal
Specific Gravity	2.40522
% Solids By Weight	100.00000%

---

Appearance	N/A
Odor Description	N/A
pH	N/A
Water Solubility	N/A
Flammability	N/A
Flash Point	N/A
Viscosity	N/A
Lower Explosion Level	N/A
Upper Explosion Level	N/A
Vapor Density	N/A
Freezing Point	N/A
Melting Point	N/A
Low Boiling Point	N/A
Evaporation Rate	N/A
Coefficient Water/Oil	N/A

## SECTION 10) STABILITY AND REACTIVITY

### Stability

Stable under normal storage and handling conditions.

### Conditions To Avoid

Avoid heat, sparks, flame and contact with incompatible materials

### Hazardous Reactions/Polymerization

Will not occur. No data available.

### Incompatible Materials

Strong bases, acids, and oxidizing agents.

### Hazardous Decomposition Products

Oxides of carbon.

## SECTION 11) TOXICOLOGICAL INFORMATION

### Acute Toxicity

Harmful in contact with skin

May be harmful if swallowed

The Acute Toxicity Estimate (ATE) for an oral exposure to this mixture is 119048 mg/kg body weight

The Acute Toxicity Estimate (ATE) for a dermal exposure to this mixture is -1 mg/kg body weight

The Acute Toxicity Estimate (ATE) for an inhalation (vapour) exposure to this mixture is >20 mg/l

#### **Aspiration Hazard**

Based on available data, the classification criteria are not met.

#### **Carcinogenicity**

May cause cancer

#### **Germ Cell Mutagenicity**

Based on available data, the classification criteria are not met.

#### **Reproductive Toxicity**

May damage fertility or the unborn child

#### **Respiratory/Skin Sensitization**

May cause allergy or asthma symptoms or breathing difficulties if inhaled

May cause an allergic skin reaction

#### **Serious Eye Damage/Irritation**

Causes serious eye damage

#### **Skin Corrosion/Irritation**

Causes severe skin burns and eye damage

#### **Specific Target Organ Toxicity - Repeated Exposure**

Causes damage to organs through prolonged or repeated exposure.

#### **Specific Target Organ Toxicity - Single Exposure**

May cause respiratory irritation

#### **Likely Routes of Exposure**

Inhalation, Ingestion, Skin contact, Eye contact

0001317-65-3    CALCIUM CARBONATE

LD50 (oral, rat): 6450 mg/kg (10; unconfirmed)

## **SECTION 12) ECOLOGICAL INFORMATION**

#### **Toxicity**

Based on available data, the classification criteria are not met.

#### **Persistence and Degradability**

No data available.

#### **Bioaccumulative Potential**

No data available.

#### **Mobility in Soil**

No data available.

#### **Other Adverse Effects**

No data available.

## **SECTION 13) DISPOSAL CONSIDERATIONS**

#### **Waste Disposal**

It is the responsibility of the user of the product to determine at the time of disposal whether the product meets local criteria for hazardous waste. Waste management should be in full compliance with national, state and local laws. Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes.

## SECTION 14) TRANSPORT INFORMATION

	U.S. DOT Information	IMDG Information	IATA Information
UN Number:1866 Resin solution	UN1759	UN1759	UN1759
Proper shipping name:	Corrosive solids, n.o.s.	Corrosive solids, n.o.s.	Corrosive solids, n.o.s.
Hazard Class:	8	8	8
Packaging:	II	II	II
Hazardous substance (RQ):	No Data Available		
Marine Pollutant:	No Data Available	No Data Available	
Note / Special Provision:	No Data Available	No Data Available	No Data Available
Toxic-Inhalation Hazard:	No Data Available		

## SECTION 15) REGULATORY INFORMATION

### Safety, health and environmental regulations

The product has been evaluated against the following relevant regulations: U.S.A Toxic Substance Control Act (TSCA) California Proposition 65 Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312 Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313 Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) Section 103

CAS	Chemical Name	% By Weight	Regulation List
0065997-15-1	PORTLAND CEMENT SILICATE	30.00% - 50.00%	SARA312,TSCA
0065997-16-2	CEMENT, ALUMINA, CHEMICALS	20.00% - 50.00%	SARA312,TSCA
0001317-65-3	CALCIUM CARBONATE	0.00% - 5.00%	SARA312,TSCA
0000554-13-2	LITHIUM CARBONATE	0.00% - 1.00%	SARA313, SARA312,TSCA,CA_Prop65 - California Proposition 65,CA_Prop65_Type_Toxicity_Devel op - CA_Proposition65_Type_Toxicity_De velopmental

The information in this Section does not list non-hazardous components that might have relevant CA\_Prop65 - California Proposition 65, CA\_Prop65\_Type\_Toxicity\_Cancer - CA\_Proposition65\_Type\_Toxicity\_Cancer, SARA312, TSCA regulatory values, if they are present at less than 1%. Please contact manufacturer for more information.



**WARNING:**This product can expose you to chemicals including SILICA, CRYSTALLINE, which is LITHIUM CARBONATE known to the State of California to cause cancer, and [CA\_Prop65\_Type\_Toxicity\_Develop], which is LITHIUM CARBONATE known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## SECTION 16) OTHER INFORMATION

### Glossary

ACGIH - American Conference of Governmental Industrial Hygienists; CAS - Chemical Abstracts Service ; Chemtrec - Chemical Transportation Emergency Center; DSL - Domestic Substances List; ESL- Effects screening levels; GHS - "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations; HMIS - Hazardous Material Information Service; IATA - Dangerous Goods Regulations (DGR) for the air transport (IATA); IMDG - International Maritime Dangerous Goods Code; LC - Lethal



Concentration; LD - Lethal Dose; NFPA - National Fire Protection Association; OEL - Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL - Permissible Exposure Limit; SARA 313 - Superfund Amendments and Reauthorization Act, Section 313; SCBA - Self Contained Breathing Apparatus; ppm - parts per million; STEL - Short-term exposure limit; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act Public Law 94-469; TWA - Time-weighted average; US DOT- US Department of Transportation.

### Version 1.0:

Revision Date: July 27, 2023

First Edition.

### Full text of H-Statements referred to under Section 3

- H320 Causes eye irritation
- H318 Causes serious eye damage
- H314 Causes severe skin burns and eye damage
- H332 Harmful if inhaled
- H302 Harmful if swallowed
- H312 Harmful in contact with skin
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled
- H317 May cause an allergic skin reaction
- H350 May cause cancer
- H373 May cause damage to organs through prolonged or repeated exposure
- H413 May cause long lasting harmful effects to aquatic life
- H335 May cause respiratory irritation
- H360 May damage fertility or the unborn child
- H401 Toxic to aquatic life

---

### DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.