

PAVER PROTECTION PROGRAM **SELECTION GUIDE**



PAVER SEAL ULTRA SHINE PAVER GUARDIAN PAVER SEAL PAVER SEAL & SHINE X TENON TENON X TENON X TENON **SOLVENT-BORNE** • Non-gloss finish that won't change · Color enhancing, darkens the color • Color enhancing, adds a rich "wet-• Color enhancing, darkens the color

- appearance of pavers
- Natural-looking invisible protection
- Non-staining, non-yellowing
- Repels water, with early water repellency
- Once cured, pronounced water beading effect
- Protects from effects of rain and other water penetration, chemicals, salt, freeze-thaw, and smog
- · Pavers, brick, burnished or splitfaced block, natural and synthetic stone, stucco, and other cementitious materials

- and adds matte finish
- Non-staining, non-yellowing
- · Minimizes spalling and aggregate pops by penetrating into the surface of the concrete or exposed aggregate to fill gaps and voids
- · Forms a membrane to increase protection from damaging freezethaw cycles, deicing salts, efflorescence, and chemical erosion
- Final seal for paving stone, colored concrete, architectural concrete, natural stone, and brick

- look" gloss
- Non-staining, non-yellowing
- Minimizes spalling and aggregate pops by penetrating into the surface of the concrete or exposed aggregate to fill gaps and voids
- · Protects surfaces from effects of rain water penetration, airborne pollutants, most chemicals, and contaminants while making surfaces easier to clean
- Final seal for paving stone, colored concrete, architectural concrete, natural stone, and brick

- and adds high gloss "wet-look" finish to the applied surfaces
- Non-staining, non-yellowing
- Forms a membrane to increase protection from damaging freezethaw cycles, deicing salts, efflorescence, and chemical erosion
- Final seal for paving stone, colored concrete, architectural concrete, natural stone, and brick

APPLICATION						
Finish	Invisible	Matte	Gloss	High Gloss		
Temperature Range	Best above 40°F	Best between 40°F-100°F	Best between 40°F-100°F	Best between 40°F-100°F		
VOC	> 700 g/L	< 700 g/L	< 700 g/L	< 700 g/L		
Typical Drying Time @ 70°F	1-2 hour (touch) 2-4 hours (traffic)	1 hour (touch) 2 hours (traffic)	1 hour (touch) 2 hours (traffic)	1 hour (touch) 2 hours (traffic)		
Product Classification	Waterproofing Sealers & Treatments	Curing & Sealing Compound	Curing & Sealing Compound	Curing & Sealing Compound		
Dosage Rate	40-200 SF/GAL	200-350 SF/GAL	200-350 SF/GAL	250-400 SF/GAL		

For Technical Product Data, Industry Standards, and Material Safety Data Sheets on all of the Tenon™ products, please visit our website at www.tccmaterials.com



PAVER PROTECTION PROGRAM SELECTION GUIDE



				SPEC BEENDED CONSTRUCTION PRODUCTS		
USES	PAVER GUARDIAN WB	PAVER SEAL PRO WB	PAVER SEAL & SHINE PRO WB	PAVER WASH		
	Paver Guardian WB	Paver Seal Pro WB	TENON Paver Seal & Shine Pro WB	TENON Paver Wash Prove Wash		
S	WATERBORNE					
ADVANTAGES/USES	 Non-gloss finish that won't change the surface appearance Natural-looking invisible protection Non-staining, non-yellowing, dries tack-free Water-bourne formula provides breathable, deep-penetrating protection that does not trap moisture Protects from effects of rain and other water penetration, chemicals, salt, freeze-thaw, and smog Exterior, above-grade applications Excellent for driveways and garage prone to salt damage from vehicular traffic 	 Color enhancing, natural, non-gloss finish Non-staining, non-yellowing Chemically reactive formulation that bonds to the capillaries of the substrate providing water repellency and color enhancement while remaining breathable Ideal for pavers and natural or synthetic stone veneer applications Penetrates into the concrete for a deeper, breathable protection from damaging freeze-thaw cycles, deicing salts, efflorescence, and chemical erosion 	 Color enhancing, adds a "wet-look" gloss finish Non-staining, non-yellowing Chemically reactive formulation that bonds to the capillaries of the substrate providing water repellency and color enhancement while remaining breathable Ideal for pavers and natural or synthetic stone veneer applications Penetrating formula resists wear patterns from foot traffic, vehicular traffic, and other external sources 	 Cleans and restores paver surface and color Dissolves rust & mineral deposits Removes most organic materials Prepares surfaces prior to sealing Easy to use - no mixing For use on pavers, brick, masonry, and concrete 		
APPLICATION						
Finish	Invisible	Natural	Gloss	N/A		
Temperature Range	Best between 50°F-90°F	Best between 40°F-100°F	Best between 40°F-100°F	Best between 50°F-90°F		
VOC	< 250 g/L	< 350 g/L	< 350 g/L	0 g/L		
Typical Drying Time @ 70°F	2-4 hours	1 hour (touch) 2 hours (traffic)	1 hour (touch) 2 hours (traffic)	N/A		
Product Classification	Waterproofing Sealers & Treatments	Curing & Sealing Compound	Curing & Sealing Compound	Mild Acidic Cleaner		
Dosage Rate	40-200 SF/GAL	200-500 SF/GAL	200-500 SF/GAL	150-250 SF/GAL		

For Technical Product Data, Industry Standards, and Material Safety Data Sheets on all of the Tenon™ products, please visit our website at www.tccmaterials.com