





	VINYL CEMENT PATCH	AKONAKOTE® POURABLE CONCRETE PATCH	INSTANT PATCHING CEMENT	PRE-MIXED CONCRETE & STUCCO PATCH
				
USES & ADVANTAGES	<ul style="list-style-type: none"> • Superior bond • High strength • Polymer-modified • Sets in 24 hours • Trowelable from featheredge up to ½” per layer 	<ul style="list-style-type: none"> • Patch seams, holes, and cracks • Use to prepare floors for resurfacing • Flowable/pourable • Correct defects up to ½” 	<ul style="list-style-type: none"> • Self bonds to existing concrete • Ideal for deep repairs • Sets in just 90 minutes • Correct defects up to 2” or up to 5” when mixed with pea gravel 	<ul style="list-style-type: none"> • Ready to use • Easy to apply • Durable • Concrete or masonry surfaces • Gray color • Correct defects up to ¼”
COVERAGE	<ul style="list-style-type: none"> • 10 lb. will yield 10 sq. ft. at ⅛” thickness • 25 lb. will yield 25 sq. ft. at ⅛” thickness • 40 lb. will yield 40 sq. ft. at ⅛” thickness 	<ul style="list-style-type: none"> • 50 lb. will yield 50 sq. ft. at ⅛” thickness 	<ul style="list-style-type: none"> • 10 lb. fills a crack 1” wide x ½” deep (30 ft. length) or 10 sq. ft. at ⅛” thickness 	<ul style="list-style-type: none"> • 1 qt. will yield 3 sq. ft. at ⅛” thickness • 1 gal. will yield 12 sq. ft. at ⅛” thickness
APPLICATION				
Interior & Exterior	X	X	X	X
Fix Defects Prior to Resurfacing	X	X	X	
Pourable/Flowable		X		
Can Be Extended For Deeper Repairs			X	
Can Be Applied In Multiple Layers For Deeper Repairs	X			X
Overhead Applications				
Trowelable to Featheredge	X	X		X
Fast-Setting			X	
Ready to Use (No Mixing)				X
Preblended Mixing Liquid:	Water only	Water only	Water or Bonding Additive	
For Concrete Surfaces	X	X	X	X
For Mortar, Stucco, Stone				X
For Technical Product Data, Industry Standards, and Material Safety Data Sheets on all of the Akona® products, please visit our website at www.menards.com				