





# SPECIALTY PRODUCT SELECTION GUIDE

	MEDIUM-DUTY REFRACTORY MORTAR	NON-SHRINK GROUT	GLASS BLOCK MORTAR	INSTANT ANCHORING CEMENT	INSTANT WATER STOP
USES & ADVANTAGES	<ul style="list-style-type: none"> <li>For fireplaces, fire pits, flues, etc.</li> <li>Good for applications up to 2550°F</li> <li>Air entrained for freeze-thaw resistance</li> <li>One hour working time</li> <li>ASTM C199</li> </ul>	<ul style="list-style-type: none"> <li>Capable of handling high load transfers</li> <li>MN DOT approved</li> <li>Non-Shrink Grouts</li> <li>ASTM C1107</li> <li>Corps of engineers spec. CRD-C 621</li> </ul>	<ul style="list-style-type: none"> <li>For use with glass block in shower or bathroom walls</li> <li>High-strength, white mortar</li> <li>Minimizes joint shrinkage</li> <li>Mix with bonding additive for exterior applications</li> </ul>	<ul style="list-style-type: none"> <li>Expands as it hardens</li> <li>Sets handrails, bolts, poles, and fixtures</li> <li>Use with concrete or masonry</li> <li>Sets in 20 minutes</li> </ul>	<ul style="list-style-type: none"> <li>Bonds well to wet walls</li> <li>Sets in just 3-5 minutes</li> <li>Plugs holes in walls</li> <li>Seals water flow in basements</li> <li>Great for swimming pool repairs</li> </ul>
COVERAGE	<ul style="list-style-type: none"> <li>50 lb. bag yields .5 cu. ft. of wet mortar</li> <li>Will lay 80-100 standard fire bricks at 1/8" joint thickness</li> </ul>	<ul style="list-style-type: none"> <li>50 lb. bag yields 0.45 cu. ft., at a flowable consistency of wet mortar</li> </ul>	<ul style="list-style-type: none"> <li>50 lb. bag yields .5 cu. ft. of wet mortar</li> </ul>	<ul style="list-style-type: none"> <li>10 lb. yields 170 cu. in. or anchors 2 fixtures in a 2" diameter hole with a depth of 2"</li> </ul>	<ul style="list-style-type: none"> <li>10 lb. yields 18 cu. in. or a crack 1" deep by 1/4" wide and 6' long</li> <li>25 lb. yields 45 cu. in. or a crack 1" deep by 1/4" wide and 15' long</li> </ul>
APPLICATION					
Interior & Exterior	X	X	X	X	X
Preblended: Just Add Water	X	X	X	X	X
Fast-Setting				X	X
Setting Fireplace Masonry Units	X				
Setting Glass Block			X		
Lead Transfer & Base Weight Distribution		X			
Setting Large Fixtures (6-12" diameter hole)					
Setting Small Fixtures (2-6" diameter hole)		X		X	
High Strength/Bond	X	X	X	X	X
Expands As It Sets					
Low/Non-Shrink		X	X	X	X

# SPECIALTY PRODUCT SELECTION GUIDE

	POWER PATCH PRO	FAST-SETTING ANCHORING EPOXY	WET & COLD CONCRETE MASONRY LOC	RAPID LOC CONCRETE & VENEER BOND
				
<b>USES &amp; ADVANTAGES</b>	<ul style="list-style-type: none"> <li>• High-strength &amp; non-sag</li> <li>• Use as adhesive or filler</li> <li>• Can be sanded and painted</li> <li>• May be used on damp surfaces</li> <li>• Easily dispensable with most standard caulking guns</li> <li>• Rapid cure, initial cure time of 3 hours</li> <li>• Repair tile underwater</li> </ul>	<ul style="list-style-type: none"> <li>• High-strength</li> <li>• Resists chemicals and solvents</li> <li>• Moisture tolerant</li> <li>• 100% solids</li> <li>• Fast-setting</li> <li>• Non-sag</li> </ul>	<ul style="list-style-type: none"> <li>• Can be applied down to 15°F</li> <li>• High-strength and fast-setting</li> <li>• Dispenses easily - even in subzero temperatures</li> <li>• Excellent adhesion</li> <li>• Fits standard caulking gun</li> <li>• Works on wet or damp environments</li> <li>• Styrene free</li> <li>• Non-sag</li> </ul>	<ul style="list-style-type: none"> <li>• Fixing of heavy objects without temporary fixation</li> <li>• Holds tight in less than 10 seconds</li> <li>• Contains no solvents or isocyanates</li> <li>• Negligible shrinkage during cure</li> <li>• Non-yellowing</li> <li>• Excellent tack-free and cure times</li> <li>• Flexible in low temperatures</li> <li>• No cracking</li> <li>• High UV resistance and color stability</li> </ul>
<b>COVERAGE</b>	• 8.6 oz. tube yields 30 lin. ft. at a 1/8" x 1/8" line	• 8.45 fl. oz. tube yields 30 lin. ft. at a 1/8" x 1/8" line	• 10 oz. tube yields 35 lin. ft. at a 1/8" x 1/8" line	
<b>APPLICATION</b>				
Interior & Exterior	X	X	X	X
Preblended: Just Add Water	Ready to Use	Ready to Use	Ready to Use	Ready to Use
Fast-Setting	X	X	X	X
Setting Fireplace Masonry Units				
Setting Glass Block				
Lead Transfer & Base Weight Distribution				
Setting Large Fixtures (6-12" diameter hole)				X
Setting Small Fixtures (2-6" diameter hole)	X	X	X	
High Strength/Bond	X	X	X	X
Expands As It Sets				
Low/Non-Shrink		X	X	X