

HARDSCAPE/LANDSCAPE SELECTION GUIDE

	LANDSCAPE LOC MULCH & ROCK BOND	TECHMIX PREMIUM COUNTERTOP MIX	TENON REFRACTORY MORTAR	TENON SELF-LEVELING RESURFACER	TENON PARTIAL DEPTH CONCRETE PATCH
					
FEATURES	• Easy to apply with sprayer • Ready to use/no dilution • Reaches full bond in 24-48 hours • Goes on white and dries clear • Allows surface to drain and breathe • Environmentally safe • Non-toxic - safe for plants and animals • Low VOC and EPA compliant	• Polymer modified • Air entrained, freeze-thaw durable for exterior use • High-strength • 4,000 psi at 24 hours • 10,000 psi at 28 days • Self-leveling consistency • Can be demolded in 18-24 hours • Just add water	• Good for applications up to 2250°F • Indoor/outdoor applications • Air-entrained for freeze-thaw resistance • One hour working time • Great workability and high-strength • Meets or exceeds ASTM C199 • Hydraulic mortar, once cured becomes water insoluble and acid resistant	• Sets in approximately 75-90 minutes • Provides a smooth, hard, flat surface • Underlayment or wear surface • Accepts foot traffic in 6 hours • Applications from < 1/8 inch to 2 inch	• Preblended mixtures (2:1, 2:5:1 and 3:1 blends) • High compressive strength • Durable patching material • No pea gravel • Meets ASTM C387 for high-early and normal strength
USES & ADVANTAGES	• Interior/exterior locations • Edges/borders, trees, plant beds, walks, driveways, slopes, leaf piles, erosion • Control of dust and erosion on gravel roads and commercial job sites	• Precast countertops • Outdoor kitchen tops • Precast wall caps • Precast mantels • Precast lintels	• Outdoor fireplaces and fire pits • Setting clay flue liners • Set or parging of smoke chambers	• New concrete floor slabs with unacceptable finishes • Damaged existing concrete • Interior and exterior concrete applications	• Paver bonding mortar • Slab stone setting mortar • Partial depth repair of concrete pavements • Shallow depth repairs between 1/2-2 inches
FOR BEST PERFORMANCE	• Apply when temperatures are above 50°F • Apply when no rain, wind, or frost is forecasted for 24 hours	• Apply when temperatures are above 50°F • Minimum thickness 1.5 inches • Maximum thickness 8 inches • Do not exceed water limits	• Do not apply in direct sunlight • Do not apply on hot or windy days • Do not apply when rain is forecasted within 24 hours • Mix only the amount that can be placed in 60 minutes	• Do not over-trowel or overdo work • Apply when temperatures are above 50°F-90°F • Apply only to surfaces that are frost free	• Use a mechanical batch mixer • Pre-wet surface just prior to application • Do not overwork the concrete mixture
SIZE	• 1 gal bottle • 5 gal pail	• 50 lb bag - gray • 50 lb bag - white	• 10 lb pail • 50 lb bag	• 50 lb bag - gray	• 50 lb bag

HARDSCAPE/LANDSCAPE SELECTION GUIDE

	TENON INSTANT HYDRAULIC CEMENT	TENON INSTANT ANCHORING CEMENT	TENON CONCRETE & MASONRY DISSOLVER	TENON RESTORATION CLEANER	TENON SALT BARRIER
					
FEATURES	• Bonds to wet walls • Sets in 3-5 minutes • Just add water, mix and use • Stops seepage leaks • Interior and exterior use • Above and below grade • Paintable when cured	• Expands as it hardens to set securely • Accelerated, sets in approximately 20 minutes • Excellent flowability and workability • Add water, mix and use	• Ready to use (no mixing or diluting) • Begins to work immediately upon application • 100% biodegradable • Non-toxic to plants and vegetation • Does not contain any harmful acids • Non-corrosive and non-fuming	• Cleans and restores • Dissolves mineral deposits • Surface preparation product • Ready to use	• Natural looking invisible protection • Ready to use (no diluting) • Dries tack free • High alkali resistance • Easy to apply with sprayer and roller • Protects from effects of rain and other water penetration, salt, freeze-thaw and smog
USES & ADVANTAGES	• Plugs holes in walls • Seals water flow in ponds or fountains • Swimming pool repairs	• Interior/exterior • Sets handrails, bolts, poles and fixtures	• Removes unwanted Portland cement-based residue • Safely removes mortar from painted surfaces	• Brick • Masonry • Concrete • Precast concrete elements • Retaining walls	• Above grade exterior applications • Vertical or horizontal applications • Concrete, masonry, pavers, brick, retaining walls, stucco, block, stone, and other cementitious materials
FOR BEST PERFORMANCE	• Apply only to surfaces that are frost free and above 40°F • Do not apply on painted surfaces • Mix with clean water only	• Do not apply in temperatures below 40°F • Let set for one hour minimum before applying torque to bolt or fixture	• Apply only to dry surfaces • Do not allow to dry on surfaces • Allow to penetrate 10-15 minutes • Rinse once concentrate has begun to soften	• Always wet surface just prior to application • Let the cleaner stand for 3-5 minutes • Do not allow product to dry on surface	• Do not apply when rain is expected within 4-6 hours • Cleaned or washed surfaces must dry 3-7 days prior to application
SIZE	• 10 lb pail • 50 lb pail	• 10 lb pail • 50 lb pail	• 28 oz sprayer • 1 gal bottle • 5 gal pail	• 1 gal bottle • 5 gal pail	• 1 gal bottle • 5 gal pail • 55 gal drum