

1. PRODUCT NAME

Conproco® Color K-88 Admix

2. MANUFACTURER

TCC Materials®
2025 Centre Pointe Blvd.
Mendota Heights, MN 55120 USA
Phone: 1.651.688.9116
Web: tccmaterials.com

3. PRODUCT DESCRIPTION

Conproco Color K-88 Admix is a 100% acrylic admixture for cementitious materials, formulated to provide color.

Features and Benefits

- Provides excellent dispersion of color through mix
- 14 natural earth tone colors
- Reduces need to moist cure materials in most cases
- Reduces shrinkage induced cracking
- Promotes chemical adhesion to substrate
- Increases compressive & tensile strengths
- Increases freeze/thaw resistance
- Increases density & improves resistance to water entry

When/Where to Use

- White Conpro Stucco, to obtain Masonry Series Colors. Refer to Conproco Product Color Selection Guide
- Color K-88 Admix can be used with Conproco products Structural Skin, Plastermix & Pro Masonry Décor Seal, to achieve similar, but not identical to Conpro Stucco

4. TECHNICAL DATA

| Typical Values • K-88 Admix | | | |
|---|---------------------------------------|---------|---------|
| Physical State & Appearance | Colored liquid | | |
| Base | Aqueous | | |
| Polymer | 100% acrylic | | |
| Odor | Ammoniacal | | |
| pH | >9.5 | | |
| Percent Solids by Weight | 45 - 65% by weight dependent on color | | |
| Density of Liquid Coatings (ASTM D1475) | 8.4 lbs. / gal. | | |
| Compressive Strength (ASTM C109) | 7 days | 14 days | 28 days |
| Design mix without Color K-88 Admix - psi | 2725 | 3375 | 3725 |
| Design mix with Color K-88 Admix - psi | 3400 | 4150 | 4700 |
| Percent increase - % | 25 | 23 | 26 |

Typical Values • K-88 Admix cont.

| Tensile Strength (ASTM C307) | 7 days | 14 days | 28 days |
|---|--------|---------|---------|
| Design mix without Color K-88 Admix - psi | 95 | 360 | 360 |
| Design mix with Color K-88 Admix - psi | 385 | 390 | 400 |
| Percent increase - % | 30 | 8 | 11 |

Available Sizes

- 1 gallon (BOM# 115343)
- 5 gallon (BOM# 115344)

Coverage

- 1 quart per 50 lb. bag of Conproco Stucco

5. INSTALLATION

Preparation

Read all directions before starting work. Proper surface preparation is crucial to achieving a successful application.

- K-88 Admix is an admixture. Refer to the specific technical data sheet for material to be used.

Note: It is the responsibility of the installer/applicator to ensure the suitability of the product for its intended use.

Priming

- Follow the instructions of the material to which Color K-88 Admix will be added

Mixing

- Stir or vigorously shake container and pour complete contents into mix. Ensure that all of the liquid and pigment are emptied from container.

Curing

- Follow the instructions of the Conproco product to which Color K-88 Admix is added

Clean Up

Clean tools and equipment with water.

Limitations

- Do not apply if temperature of substrate is below 45°F
- Do not apply if ambient temperature is below 45°F
- Do not re-temper mixes modified with Color K-88 Admix
- Avoid contact with skin & eyes
- Avoid breathing vapors

Safety

READ THE SAFETY DATA SHEET (SDS) BEFORE USING THIS PRODUCT. SDS information is available on our website: tccmaterials.com

- In case of skin contact, wash thoroughly with soap and water.
- For eye contact, flush immediately with a high volume of water for at least 15 minutes and contact a medical professional
- For respiratory problems, remove person to fresh air.

- If respiratory difficulty persists, contact a medical professional

Cautions

Read complete cautionary information printed on product container prior to use.

This Product Data Sheet has been prepared in good faith on the basis of information available at the time of publication. It is intended to provide users with information about and guidelines for the proper use and application of the covered Akona brand product(s) under normal environmental and working conditions. Because each project is different, TCC Materials cannot be responsible for the consequences of variations in such conditions, or for unforeseen conditions.

6. AVAILABILITY

To locate Conproco products in your area, please contact:

Phone: 1.651.688.9116
Email: info@tccmaterials.com

7. WARRANTY

Seller warrants that its product will conform to and perform in accordance with the product specifications. The foregoing warranty is in lieu of all other warranties, expressed or implied, including, but not limited to those concerning merchantability and fitness for a particular purpose. Because of the difficulty in ascertaining and measuring damages hereunder, it is agreed that Seller's liability to the Buyer shall not exceed the total amount billed and billable to the Buyer for the product hereunder.

| | |
|--------------------|---|
| Shelf Life | 18 months when properly stored |
| Storage Conditions | Protect from freezing. Transport and store in cool, clean, dry conditions in unopened containers. High temperature or high humidity will reduce shelf life. |
| Color | Reference Masonry Series Color Card |

| |
|---|
| KEEP PRODUCT IN CONTAINER FROM FREEZING |
| WARNING: INJURIOUS TO EYES |
| KEEP OUT OF REACH OF CHILDREN |

©Copyright 2025 TCC Materials®



2025 Centre Pointe Blvd.
Mendota Heights, MN 55120