



TENON®

Burnished Block Sealer



Enhances color & adds sheen

Tenon® Burnished Block Sealer is used as a final sealer on masonry block walls including burnish block or ground face block, architectural block, brick, slate, paving stone, terrazzo, quarry tile, and cementitious materials. It enhances the beauty, giving the surface a rich “wet-look” sheen. It forms a membrane to increase protection from damaging freeze-thaw cycles, deicing salts, efflorescence, and chemical erosion, protects surfaces from most chemicals, dirt, acids, alkali, oil, grease, foods, and airborne pollutants while making these surfaces easier to clean.

Features:

- Non-staining, non-yellowing
Ready to use (no diluting)
- Makes surfaces less dusty and easier to clean by resisting penetration of grease or rust stains on concrete surfaces
- Easy to apply with sprayer, roller, or long nap applicator
- Protects from effects of rain water penetration, chemicals, oils, salt, freeze-thaw, smog, and contaminants
- 2-hour drying time under normal conditions
- Wear patterns can be easily re-coated

Burnished Block Sealer



Application

- Apply only to surfaces when air and substrate temperatures are between 40°F-100°F (4°C-38°C) and the Burnished Block Sealer is above 50°F (10°C). For best results, avoid application in direct sunlight.
- Apply with an airless sprayer, roller, or with a long napped applicator at the rate of 300-500 sq. ft. per gal.
- Sprayers must be equipped with neoprene or other compatible fittings as the solvent can damage rubber fittings.
- Work the Burnished Block Sealer into the surface, avoiding pools, runs, sags, or the creation of lap marks. Do not over apply
- Surface should have a uniform coating.
- Allow first coating to thoroughly dry prior to application of a second coating.
- May also be used on fully cured, dry, horizontal surfaces using a low-pressure sprayer, roller, or brush.

Approximate Coverage @ 70°F (21°C)	Sq. Ft. / Gal.	M ² / L
Burnished Block	250 - 500	6.1 - 12.3
Horizontal Surfaces	250 - 500	6.1 - 12.3

Available In:

Tenon[®] Burnished Block Sealer is available in 1 gal. bottle, 5 gal. pail, and 55 gal. drum.



55 Gal
BOM #114867



5 Gal
BOM #114865



1 Gal
BOM #114864

For professional use only.

It is the responsibility of the installer/applicator to ensure the suitability of the product for its intended use. For technical assistance, please contact TCC Materials. To acquire technical and safety literature, please visit our website.