



TENON®

Paver Seal



Enriches & Enhances Natural Color

Tenon® Paver Seal protects and enhances pavers and other cementitious surfaces with a durable, UV-resistant methacrylate coating and matte finish. It resists freeze-thaw damage, salts, chemicals, and stains while enriching color and making surfaces easier to clean. Suitable for pavers, concrete, brick, and tile.

Features:

- Enhances natural color with a matte, non-yellowing finish
- Ready to use; solvent-based for strong surface protection
- Penetrates to reduce spalling, aggregate pops, and dusting
- Resists grease, rust, chemicals, salts, and pollutants
- Improves freeze-thaw and water resistance
- Easy to apply by sprayer, roller, or applicator
- Dries in about 2 hours for traffic
- Simple to recoat in worn areas

Paver Seal



Application

- Apply only when air and substrate temperatures are between 40°F-100°F (4°C-38°C) and the Paver Seal is above 50°F (10°C). For best results, avoid application in direct sunlight.
- Apply with low-pressure sprayer, with roller, or with a short-napped applicator at the rate of 200-350 sq. ft. per gal. Sprayers must be equipped with PVC, viton, or other compatible fittings and hoses as solvents can damage rubber.
- Work the Paver Seal into the surface, avoiding pools, runs, or sags.
- For large areas, an airless sprayer can be used and backrolling recommended. Sprayers must be equipped with PVC, viton, or other compatible fittings as the solvent can damage rubber fittings.
- Surface should have a uniform coating.
- Allow first coating to thoroughly dry prior to application of a second coating.

Approximate Coverage @ 70°F (21°C)	Sq. Ft. / Gal.	M ² / L
Pavers & Smooth Concrete	200 - 300	4.9 - 7.4
Decorative & Broomed Concrete	250 - 350	2.4 - 8.6
Natural Stone	200 - 300	4.9 - 7.4
Concrete Block	200 - 300	4.9 - 7.4

Available In:

Tenon[®] Paver Seal is available in 1 gal. bottle, 5 gal. pail, and 55 gal. drum.



55 Gal
BOM #129551



5 Gal
BOM #129720



1 Gal
BOM #129730

For professional use only.

It is the responsibility of the installer/applicator to ensure the suitability of the product for its intended use. For technical assistance, please contact TCC Materials. To acquire technical and safety literature, please visit our website.