



TENON[®]

Vinyl Concrete Patch



Polymer-Modified Patch

Tenon® Vinyl Concrete Patch is a polymer-modified, Portland cement-based patching compound used to repair minor surface imperfections in concrete. Suitable for interior and exterior applications from feather edge to 2 in. (51 mm) thick per lift. Supports foot traffic in 8-12 hours, wheeled traffic in 48 hours.

Features:

- Featheredge to 2 in. (51 mm) in thickness
- Polymer-modified for higher bond strength
- Portland-cement based
- High-strength with superior workability
- Easy application
- Excellent resistance to deicing salts
- Shrinkage compensating



Application

90°F (10°C-32°C) for 24 hours prior to application and 48 hours thereafter. Do not apply in direct sunlight on hot, windy days, or when rain is forecasted within 24 hours.

1. Just prior to application, pre-dampen surface to be repaired with clean water to saturated surface dry (SSD) condition with no standing water remaining. Apply Vinyl Concrete Patch with a steel trowel onto properly prepared surface.
2. To reduce shrinkage and cracking, do not exceed thickness of 2 in. (51 mm) per layer. If a higher build-up is needed, allow a minimum of 24 hours drying time between each lift.
3. Vinyl Concrete Patch may also be extended for placements greater than 2 in. (51 mm) in depth. Pre-blend washed SSD of 3/8 in. (9.5 mm) graded aggregate into Vinyl Cement Patch mix at a ratio of:
 - » 4 lb. (1.8 kg) aggregate per 10 lb. (4.5 kg) pail of powder.
 - » 20 lb. (9 kg) aggregate per 50 lb. (22.7 kg) bag of powder.
4. Clean the surface of the trowel often with water and use a "light touch" when finishing the surface. Do not over trowel. If a textured finish is desired, brush in one direction with a soft-bristled brush or broom while patch is still soft. This product should not be over-troweled or over-worked.
5. Protect the surface from use until patch is completely hard and set. On average, supports foot traffic in 8-12 hours, wheeled traffic in 48 hours depending upon temperatures and humidity.

Available In:

Tenon[®] Vinyl Concrete Patch is available in a 10 lb. pail and 50 lb. bag.



50 lb. bag
BOM #120681



10 lb. pail
BOM #127634

For professional use only.

It is the responsibility of the installer/applicator to ensure the suitability of the product for its intended use. For technical assistance, please contact TCC Materials. To acquire technical and safety literature, please visit our website.