



TENON[®]

Waterproofin & Crack Isolation Membrane



Flexible, Load-Bearing Liquid Membrane

Tenon® Waterproofing & Crack Isolation Membrane is an advanced latex polymer-based technology used as a waterproofing underlayment membrane or as part of a crack isolation system.

Features:

- Flexible with exceptional elongation
- Waterproof
- Solvent free and VOC compliant
- Interior and exterior
- Horizontal and vertical applications
- Will not support mold growth
- Ready to use - no mixing required
- Flood test in 12 hours
- Allows light foot traffic in 4-6 hours
- Anti-fracture protection up to 1/8 in. (3 mm)
- Exceeds ANSI A118.10 and A118.12



TENON®

Waterproofin & Crack Isolation Membrane



Uses

- Above and below grade walls or floors
- Swimming pools, spas, and fountains
- Food processing areas
- Balconies over unoccupied space
- Shower stalls and tub surrounds
- Light commercial bathrooms
- Steam rooms
- Crack isolation membrane

Recommended Substrates

- Concrete **
- Brick masonry **
- Cement Backer Unit (CBU) **
- Mortar beds **
- Gypsum wall board*
- Exterior grade plywood*
- OSB*
- Plaster*
- Countertops*
- Gypsum-based cement topping (min. 2000 psi compressive strength*)
- Existing ceramic tile and resilient flooring*

* Interior only

** Suitable as a load bearing substrate for installation of direct adhered masonry veneer applications.

Available In:

Tenon® Waterproofing & Crack Isolation Membrane is available in a 1 gal. tub and 5 gal. tub.



5 Gal. Tub

BOM #120676



1 Gal. Tub

BOM #120675

For professional use only.

It is the responsibility of the installer/applicator to ensure the suitability of the product for its intended use. For technical assistance, please contact TCC Materials. To acquire technical and safety literature, please visit our website.



TCC Materials
2025 Centre Pointe Blvd
Mendota Heights, MN 55120

Phone: 651.688.9116
Email: info@tccmaterials.com
Web: tccmaterials.com