



TENON[®]

Salt Barrier WB



Invisible Protection

Tenon[®] Salt Barrier WB is designed to protect & extend the life of concrete, masonry, pavers, retaining walls and other cementitious surfaces by protecting from the damaging effects of salt and de-icing chemicals without affecting the finished look. It provides a natural finish that maintains the original appearance of driveways, patios, garage floors, block walls, and other concrete or masonry surface. This clear, water-based formula penetrates and reacts chemically within the capillaries of the surface to protect against deicing salts, moisture penetration, spalling, freeze-thaw damage, efflorescence, and chemical erosion. Salt Barrier WB is used for above-grade exterior applications that are not subject to hydrostatic pressure.

Uses:

- Above-grade exterior applications
- Vertical or horizontal applications
- Fully-cured new or existing applications
- Concrete, masonry, pavers, brick, retaining walls, stucco, block, stone, and other cementitious materials
- Excellent for driveways and garages prone to salt damage from vehicular traffic



TENON®

Salt Barrier WB



Application

1. Apply with low-pressure sprayer with a wet-fan type spray nozzle, power roller with 1" nap, or brush.
2. On vertical surfaces, apply using a flooding application from the bottom up. Apply evenly and sufficiently to wet the substrate completely with a minimum 6-8 in. (5 cm) run-down below the spray pattern.
3. On horizontal surfaces, the liquid sealer should pond on the surface for at least 5 seconds before being absorbed. Roll out any pools that accumulate on the surface after 5 minutes. If any dry areas form before 5 minutes, apply an additional light coat to those dry areas.
4. It is important to spray or roll the surface to evenly spread the sealer. Surface should have a uniform wet-look until the sealer dries.
5. Very porous surfaces may require 2 coats of Salt Barrier WB, wet on wet application. It is better to apply 2 thin coats than 1 heavy coat.
6. When applying to split-face block, be sure the block is dry to allow for good penetration with no run-down. If applied to damp block, the water on the surface may prevent proper penetration which may prevent it from achieving a natural look.

Approximate Coverage @ 70°F (21°C)	Sq. Ft./Gal.	M ² /L
Pavers & Smooth Concrete	150 - 300	3.6 - 7.3
Retaining Wall & Concrete Block	40 - 100	0.98 - 2.4
Exposed Aggregate	100 - 200	2.4 - 4.9
Bridge Decks/Ramps	100 - 200	2.4 - 4.9

Note: Coverage may vary due to porosity and condition of substrate. Very porous surfaces may require 2 coats, wet on wet.

Available In:

Tenon® Salt Barrier WB is available in a 1 gal. (3.78 L) bottle, 5 gal. (18.93 L) pail, and 55 gal. drum (208 L).



55 Gal.
BOM #129587



5 Gal.
BOM #129850



1 Gal.
BOM #129840

For professional use only.

It is the responsibility of the installer/applicator to ensure the suitability of the product for its intended use. For technical assistance, please contact TCC Materials. To acquire technical and safety literature, please visit our website.



TCC Materials
2025 Centre Pointe Blvd
Mendota Heights, MN 55120

Phone: 651.688.9116
Email: info@tccmaterials.com
Web: tccmaterials.com