TENON®

Cure & Seal



Cures, seals, & dustproofs concrete

Tenon® Cure & Seal is a clear, non-yellowing, fast drying acrylic compound. No fillers, oils, waxes or saponifiable resins are contained in the mixture. It is used for curing, sealing, and dustproofing of freshly-placed and/or existing concrete, terrazzo, brick, stone, architectural concrete, and other cementitious materials. Forms a membrane film on new concrete to seal and retain hydration water, providing optimum curing of the substrate, resistance to abrasion, damage caused by salt, oil, grease, mild acids, alkali, and stains from soot, smog, fumes, and gases.

Features:

- Cures in 1-2 hours
- Increases optimum cure of new concrete
- Protects concrete surfaces from dirt & damage
- Enhances colors, darkens the appearance of concrete, brick, stone terrazzo, and exposed aggregate
- Ready to use (no diluting)
- Goes on clear, dries clear
- Chemical resistant
- Easy to apply with sprayer or roller
- Makes job site clean-up easier, construction debris do not adhere
- Compatible with many resilient tile & carpet adhesives, and can improve adhesion effiency for longer life to the floor covering

TENON®

Cure & Seal



Application

Apply when both air and surface temperatures are above 40°F (4.4°C) and the Cure & Seal is above 50°F (10°C). For best results, apply uniformly at the specified rate of coverage. When using an airless sprayer, it should be equipped with PVC, viton, or other compatible fittings and hoses as solvents can damage rubber.

NOTE: Cure & Seal will darken the appearance of new concrete, especially if it is applied too heavily. A small mock-up in an inconspicuous area is often done to test compatibility with the substrate prior to full application.

Approximate Coverage @ 70°F (21°C)	Sq. Ft. / Gal.	M² / L
Curing	300 - 500	7.3 - 12.3
Dustproof / Seal	300 - 500	7.3 - 12.3
Second Coat	400 - 800	9.8 - 19.6
Renovation Dustproof / Seal	300 - 400	7.3 - 9.8

Available In:

Tenon® Cure & Seal is available in 1 gal. bottle, 5 gal. pail, and 55 gal. drum.



55 Gal
BOM #120932

5 Gal
BOM #120838

1 Gal
BOM #120839

For professional use only.

It is the responsibility of the installer/applicator to ensure the suitability of the product for its intended use. For technical assistance, please contact TCC Materials. To acquire technical and safety literature, please visit our website.

TCC MATERIALS

TCC Materials
2025 Centre Pointe Blvd
Mendota Heights, MN 55120

Phone: 651.688.9116
Email: info@tccmaterials.com
Web: tccmaterials.com